

Required documents for flooring

V3 05 02 14

As a manufacturer of flooring you are required to provide accompanying commercial documents (ACD) and declaration of performance (DOP) outlining the performance of your cladding.

The untreated ACD and DOP needs the species, density, grade, durability class changing.

The treated ACD and DOP need the above + the preservative used, penetration rate and retention value adding.

Flooring should be ordered and treated to a minimum of Use Class 1 for dry upper floors (insect only) and Use Class 2 (insect and fungi) for floors with a risk of wetting and ground floors.

Note: NPD means No Product Declaration.

Pack label

FOR UNTREATED SOFTWOOD



R T Crawford Limited
15

BS EN 14342:2013
Solid wood flooring

Accompanying commercial documents – to go with products

FOR UNTREATED SOFTWOOD FLOORING

	
R T Crawford Limited	
15	
BS EN 14342:2013	
Solid wood flooring	
Use	Internal
Species	WPPA
Sizes	As delivery note, invoice and/or purchase order and customer specification
Grade	A
Reaction to fire linked with the minimum mead density and the minimum overall thickness	
D-s2, d0	450 kg/m³ 18 mm
Emission (release) of formaldehyde	E1
Release of dangerous substances	NPD
Natural durability (not treated)	Class 4
Durability for treated timber (if treated)	NPD
Slipperiness	NPD
Thermal conductivity	NPD
Emission of pentachlorophenol	NPD
Breaking strength	NPD

Construction Products Regulation

DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type:

Wood flooring for internal use

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

As the delivery note, invoice and/or customer specification

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Planed and profiled wood flooring for internal use

4. Registered name and contact address of the manufacturer as required pursuant to Article 11(5):

R T Crawford, Lisbellaw, Co. Fermanagh, BT94 5DX

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 14342:2013

We have performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 4 and issued the certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire linked with the minimum mead density and the minimum overall thickness	D-s2, d0 450 kg/m³ 18 mm	EN 14342:2013
Emission (release) of formaldehyde	E1	
Release of dangerous substances	NPD	
Natural durability (not treated)	Class 4	
Durability for treated timber (if treated)	NPD	
Wood preservative (if treated)	NPD	
Penetration class (if treated)	NPD	
Retention class (if treated)	NPD	
Slipperiness	NPD	
Thermal conductivity	NPD	
Emission of pentachlorophenol	NPD	
Breaking strength	NPD	

Specific technical documentation:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Robert Allen
General Manager
Lisebellaw
26/4/2018