



Issued 08/14

VINYL SOFTSHEEN

Dulux Softsheen is a top quality washable emulsion based on unique **AkzoNobel** technology. The delicate mid-sheen finish is wipeable, easy to apply and has excellent coverage. Where condensation is a problem e.g. some kitchens and bathrooms, use **Dulux** Diamond Eggshell. Suitable for all normal interior wall and ceiling surfaces.

KEY BENEFITS

- Tough washable finish
- Fashionable mid-sheen finish
- Coverage of up to 16m²

PRODUCT INFORMATION

Typical Use

Suitable for all normal interior walls and ceiling surfaces but in conditions subject to frequent heavy condensation (e.g. some kitchens and bathrooms) Dulux Bathrooms or Trade Diamond Eggshell is more suitable.

Pack Size

1L, 2.5L, 5L, 10L, Promotional

Colour Range

See appropriate **Dulux** colour literature or visit dulux.ie.

Film Properties

Chemical Resistance: Not Suitable

Heat Resistance: Not suitable for use on heated surfaces, such as Radiators.

Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderately vigorous washing. Where frequent heavy condensation is likely, as in some kitchens and bathrooms, **Dulux** Bathrooms/Acrylic Eggshell is more suitable.

Composition (nominal)

Pigment: Lightfast Non-Lead Pigments.

Binder: Copolymer Emulsion

Solvent: Water.

Volume Solids

33% (nominal) colours will vary.

SURFACE PREPARATION

To get the best results with **Dulux** Vinyl Softsheen, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell** Trade **Polyfilla**.



VINYL SOFTSHEEN

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux** Vinyl Softsheen (up to 1 part clean water to 5 parts paint.) The normal finishing process is 2 full coats of **Dulux** Vinyl Softsheen, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller, conventional spray or airless spray.

As with other water-based paints, do not apply at temperatures below 7°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Sealing new or bare surfaces:: Add up to 1 part clean water to 5 parts paint.

Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.

Conventional spray application: Add up to 1 part clean water to 5 parts paint.

Airless Spray: Thinning is not required.

Spray Recommendations

Conventional Spray: satisfactory through most equipment.

Airless Spray: A typical set up for airless spray would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size of 0.38mm (15 thou) and a spray tip angle of 65°.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

This product contains max. 7g/l VOC. VOC content:

Low (0.30-7.99%).



Issued 08/14

VINYL SOFTSHEEN

FURTHER SUPPORT

If you need further support, please contact the Dulux Technical Advice Centre on [+353-21-422-0222](tel:+353-21-422-0222)

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 413) is available free on request by telephoning the **Dulux** Technical Advice Centre or by visiting dulux.ie

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel

