



Issued 03/15

EASYCARE SATINWOOD

Dulux Easycare Satinwood is 10 times tougher *than conventional Satinwood giving you a durable, hard wearing, scuff resistant finish to your wood and metal. It is easy to spread and is low odour. No undercoat is required. Being water-based, no white spirits are required for cleaning. Stay white on radiators.

KEY BENEFITS

- 10 x Tougher
- Quick Drying in 6 Hours
- Low Odour

PRODUCT INFORMATION

Typical Use

Suitable for use on interior wood and metal.

Pack Size

750ml and 2.5L

Colour Range

See appropriate Dulux Colour literature or visit dulux.ie

Film Properties

Chemical Resistance: Resistant to mild chemical fume attack but where there is actual contact with chemicals, specialist paint systems may be required. (Contact the Dulux Technical Group).

Heat Resistance: Generally resistant to heat up to 90°C, but some discolouration of light colours may occur at elevated temperatures.

Water Resistance: Resistant to the levels of atmospheric humidity present in normal interior environments and will withstand repeated washing. Not suitable for use on immersed surfaces or where there is very heavy and prolonged condensation. Suitable for use in normal kitchen and bathroom situations.

Film Thickness

Film thickness will be dependent on coverage achieved.

Wet: 50 microns

Dry: 25 microns

Composition (nominal)

Pigment: Lightfast Non-Lead Pigments.

Binder: Modified Acrylic Copolymer.

Solvent: Water.

Volume Solids

White 37% (nominal), other colours will vary.

SURFACE PREPARATION

To get the best results with Dulux Easycare Satinwood, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

AkzoNobel



Issued 03/15

EASYCARE SATINWOOD

Any surface defects should be filled with the appropriate Polycell Trade polyfilla.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Apply using a clean brush, a good quality brush that is the right size for the job will give the best results. Apply 1 or 2 coats of Dulux Easycare Satinwood. Where a strong colour change is involved, 2 or more coats maybe required. Allow 6 hours between coats. Do not spread the paint too far. Replace the lid firmly on the can and shake to ensure an airtight seal.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

Newly painted doors and windows should not be (tightly) closed until paint is fully dry.

Radiators must be turned off and only painted when cold.

APPLICATION METHOD

Brush or Roller.

As with other water-based paints, do not apply at temperatures below 7°C (as recommended by British Standard BS 6150)

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Thinning

Do not thin

Drying Times

Single coat at standard thickness:

Touch Dry: 3-6 Hours.

Recoat: 6 Hours.

Cleaning Up

After use, remove as much paint as possible from equipment before cleaning with water.

When this paint container is empty, please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating to Community RePaint. Find out more at Dulux.ie.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat: A/d): 130g/l (2010). This product contains max. 45g/l VOC. VOC Content: Low (0.30-7.99%).



Issued 03/15

EASYCARE SATINWOOD

FURTHER SUPPORT

If you need further support, please contact the Dulux Technical Advice Centre on +353-21-422-0222

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet is available free on request by telephoning the Dulux Customer Advice Centre or by visiting dulux.ie

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the Akzonobel group © Akzonobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel

