

Dene Mixer Range

TRITON

See you first thing Britain



Ease of Installation



Sequential
UNDETHEXSQM




Concentric
UNDETHEXCM



Eco
ECODETHBM
Hi-Flo
UNDETHBM

Eco Lever
ECODETHBMLE
Hi-Flo Lever
UNDETHBMLE



Cool Touch
UNDETHBMCT
Cool Touch Lever
UNDETHBMCTLE



Diverter
UNDETHBMDIV
Diverter Lever
UNDETHBMDIVLE

Specification:

	Hi-Flo Cool Touch Eco	Sequential Concentric	Diverter
Temperature Control	Thermostatic	Thermostatic	Thermostatic
Inlet Fittings	Push fit for pipe tails	Integral (nuts & olives supplied)	Push fit for pipe tails
Inlet Connection	15mm female push fit	15mm female compression	15mm female push fit
Outlet Connection	1/2" BSP male	1/2" BSP male	1/2" BSP male
Maximum Running Pressure*	5 bar	5 bar	5 bar
Minimum Running Pressure*	0.1 bar	0.1 bar	0.5 bar
Flow Rate (min pressure)	5 l/min - Hi-Flo 3 l/min - Cool Touch 5 l/min - Eco	3.9 l/min - Sequential 4.3 l/min - Concentric	5 l/min
Flow Rate 3 bar	30.0 l/min - Hi-Flo 12.5 l/min - Cool Touch 6.0 l/min - Eco	30.0 l/min - Sequential 30.0 l/min - Concentric	12.5 l/min
Optional Limiter	12 l/min - Hi-Flo 12 l/min - Cool Touch 6 l/min (factory fitted) - Eco	12.0 l/min - Sequential 12.0 l/min - Concentric	n/a

*A minimum flow rate of 8 l/min is required from each inlet pipe at the specified pressure - check before fitting the mixer valve

Features:

- All fixings to complete the job
- Appealing all chrome design
- Wide range for a variety of suites
- Good flow rates, even on a gravity system
- Durable design including ceramic disc flow control
- 3 spray pattern shower head
- Bar mixers offer lever handle option for ease of use for all the family.



WRAS
APPROVED
PRODUCT



Push fit brackets supplied with all bar mixers



Dene Tap Range

TRITON

See you first thing Britain



Basin Tap Pair*
UNDETPBAS









Basin Mono Mixer Tap*
UNDETPBAM



Bath Filler
UNDETPBF



Bath Shower Mixer
UNDEBSM



Features:

- Installer bathroom products with all the necessary fittings to complete the job from flexible tap connectors to a slotted waste
- Performance to suit a wide variety of installation conditions including gravity supplies
- Versatile enough to carry on the van, and peace of mind that householders are enjoying generous flow rates

Benefits

- Lever handles are easy to grip and turn
- Metal backnuts or horseshoe plate for secure fixing
- Flexible tap connectors
- Slotted click clack waste included*



Call: 02476 234 776 | Email: specification@tritonshowers.co.uk | Web: www.tritonshowers.co.uk