



Flexacryl Instant Repair

FOR ROOFS

Date: 05 October 2015

Fact Sheet No.: TDS00262

YOUR SMART ADVANTAGES

- Immediate waterproofer
- For wet or dry surfaces
- Contains fibres to bridge gaps

USES

Bostik Flexacryl Instant Repair for Roofs is a flexible roof coating that offers immediate waterproofing on most conventional roof substrates.

Bostik Flexacryl Instant Repair for Roofs can be brushed straight from the tin onto substrates such as old roofing felt, asphalt, bituminous roof coatings, cement, concrete, lead work, metal, brickwork, slate and rigid PVC. Bostik Flexacryl Instant Repairs for Roofs is also suitable for application to gutters and flashings. If using Bostik Flexacryl Instant Repair for Roofs on a roof or balcony subject to heavy traffic, regular use or the placing of objects such as garden furniture, promenade tiles or a similar protective material must be used.

30811945	Grey	2.5kg x 6
30811957	Black	5kg x 4
30811941	Grey	5kg x 4
30811948	White	5kg x 4
30811959	Black	20kg
30811943	Grey	20kg

Storage/Shelf Life

Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

PRODUCT CHARACTERISTICS

Colour	Black, grey, white		
Form	Brushable & trowellable paste		
Specific Gravity	1.1 approx.		
Composition	A fibre reinforced solution of an acrylic co-polymer		
Product Code	30811960	Black	1kg x 6
	30811953	Grey	1kg x 6
	30811956	Black	2.5kg x 6

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C
Service Temperature	-10°C to +85°C depending on ambient conditions
Coverage	1 – 2kg (approx.) per m ²
Drying Times	Immediate waterproofing; 2 to 3 days to dry depending on application thickness, ambient temperature and humidity.
Chemical & Water Resistance	Resistant to most salt solutions, some dilute acids and alkalis. Not resistant to oils, solvents, some detergent solutions and some glass cleaning compounds.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

Heat Flow Resistance	The cured film will not sag or flow under normal conditions
Fire Resistance	Wet: Flammable Dry: Will burn

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Flexacryl Instant Repair for Roofs refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure the roof surface is structurally sound, clean, dry and free from surface contaminants such as grease, oil, rust and dirt.
2. Remove any organic growth i.e. moss or lichen with Bostik Fungicidal Wash.
3. Most surfaces do not need to be primed.
4. New metal surfaces should be degreased with a suitable solvent. Metal surfaces with residual rust remaining after cleaning should be treated with a zinc phosphate or other suitable rust inhibitive primer. New galvanised sheeting should be primed with a suitable primer.
5. Highly porous or friable surfaces should be primed with Bostik Penetration Primer for Roofs (see separate product data sheet). Ensure that the primer is fully dry before applying Bostik Flexacryl Instant Repair for Roofs. Bostik Flexacryl Instant Repair for Roofs can be applied directly to wet surfaces once all the surface contaminants have been removed and any excess water brushed away.
6. Stir Bostik Flexacryl Instant Repair for Roofs well before use.

APPLICATION

7. Where possible we recommend using disposable brushes for the application of Bostik Flexacryl Instant Repair for Roofs.
8. Apply by brush straight from the container in a single, uniform application at a rate of 1 – 2kg per m² depending on application:
On a sloping roof: one coat at 1kg per m²
On a sloping roof which ponds: two coats at 1kg per m²
In gutters subject to scouring: two coats at 1kg per m²
9. Ensure gaps or cracks are completely covered, as Bostik Flexacryl Instant Repair for Roofs contains fibres that will bridge and seal them permanently.

CLEANING

10. Clean tools and equipment immediately after use with white spirit.
11. Dried product is difficult to remove.

PRECAUTIONS IN USE

Bostik Flexacryl Instant Repair for Roofs is not recommended for use in aquatic environments, or internally as a tanking membrane. For areas where there is regular foot traffic it is recommended that Bostik Flexacryl Instant Repair for Roofs is overlaid with promenade tiles or similar protective material.

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Flexacryl Instant Repair for Roofs in an inconspicuous area and allow to dry to determine colour suitability before commencing work.

Shade variations may occur between batches. When completing project requiring multiple tins please ensure that they are from the same batch.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Flexacryl Instant Repair for Roofs, available at www.bostik.co.uk.



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.