

Oakham 660 & 750 SPECIFICATION



GENERAL	<p>Features an exceptional outward opening door with 800mm wide entrance. An integral ramped seat alongside doorway for easy transfer. Ideal for oversized, frail and wheel chair users.</p> <p>Manufactured for maximum stability and rigidity in sanitary acrylic and 4 layers of GRP reinforcement – nominally 8.5mm thick. Bath is cradled within a substantial stainless steel 30mm square box framework. Supported by 8 heavy gauge adjustable legs 10mm dia with 45mm dia feet. Built to be free standing</p>
DOOR AND LOCK	<p>The Door and Jamb (door sides) are uniquely manufactured in powder coated Aluminium for a precision water seal. The patented dead-bolt door lock, with single lever operation requires minimum force to shut. Perfectly suitable for frail users with arthritic hands.</p>
CONFIGURATION	<p>LH & RH door hinging options (with seat on opposite side) – supplied pre-assembled with Pop-Up waste/Overflow, 2 x Grab Rails and End Panel fitted. <u>Front side of the bath is moulded in with 2 x Access Panels.</u></p>
WASTE	<p>Unique 2" diameter Pop Up waste with a <u>horizontal drain</u> for faster drainage. (Requires a Shallow In Line Waste Trap only).</p>
USER WEIGHT	<p>Maximum 35 stones/222 kilos</p>
SEAT	<p>Height – 420 Internal – 527 to 537 from the bathroom floor. Width – 525 (660 Model) – 590 (750 Model)</p>
STEP THRESHOLD	<p>165 Max / 145 Min – (55 less to inner step)</p>
DIMENSIONS	<p>660 Model: 660/713W x 1298L x 960H (overall) 750 Model: 746/800W x 1298L x 960H (overall)</p>
CAPACITY	<p>660 Model: 285 litres (unoccupied) 750 Model: 300 litres (unoccupied)</p>
WEIGHT	<p>660 Model: 65 kilos 750 Model: 74 kilos</p>