



# Sealocrete Linemarking Paint

## Linemarking Aerosol Paint

Date: 14 June 2016

Fact Sheet No.:

### YOUR SMART ADVANTAGES

- Dries in 30 minutes
- Fully cures in 24 hours
- Wide range of uses

### USES

Sealocrete Linemarking Paint Aerosols are designed to bring order to car parks and roadways where indiscriminate parking of vehicles may cause danger and impede the flow of traffic. Sealocrete Linemarking Paint Aerosols are formulated with speed of use in mind. Blended from high quality pigments, resins and fast drying solvents, it dries in 30 minutes and cures fully in 24 hours. Sealocrete Linemarking paint Aerosols can be fitted to a trolley or a hand held applicator and is ideal for use on car parks, roads, factory walkways and warehouses, playgrounds, playing fields or any ground under repair.

### PRODUCT CHARACTERISTICS

Colour	White : Yellow : Red : Blue
Form	Aerosol Paint
Specific Gravity	NA
Composition	Pigmented Acrylic resin Lead Free Pigmentation Xylene Free
Product Code	30811247 White 750ml x 12 30811246 Yellow 750ml x 12 30811248 Red 750ml x 12 30811249 Blue 750ml x 12
Storage/Shelf Life	Will keep for up to 24months when stored unopened in a cool, dry area

between +5°C to +25°C and out of direct sunlight. Protect from frost.

### TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+10°C to +30°C
Service Temperature	
Coverage	One 750ml can will give between 60 to 80 mtrs of 50mm line when used in a standard machine, depending on application weight.
Drying Times	At 20oC product dries in 30 minutes . Fully cures in 24 hours. Allow to dry for at least 24 hours before subjecting to traffic. Drying times extended at lower temperatures.
Solvent for Cleaning Up	White Spirit

### DIRECTIONS FOR USE

IMPORTANT: Before using Sealocrete Line painting Aerosols refer to the relevant Health & Safety Data Sheet, available at [www.bostik.ie](http://www.bostik.ie).

### PREPARATION

1. Surfaces must be sound, clean and free from contaminants such as dust, oil, grease and any loose material.
2. Shake the can for at least 1 minute after the agitator balls are heard rattling and again frequently during use.

### APPLICATION

3. Take care to avoid over spray onto surrounding areas, especially in windy conditions.



FM 01696  
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 [www.bostik.ie](http://www.bostik.ie)

4. Allow to dry for at least 24 hours before subjecting the markings to traffic.

#### CLEANING

5. Uncured product may be removed using cloths lightly dampened with white spirit.
6. After use clear the valve by spraying in an upright position for 1 or 2 seconds, ensuring the can is pointing away from user.

#### PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit [www.bostik.ie](http://www.bostik.ie) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Sealocrete Linemarking Paint, available at [www.bostik.ie](http://www.bostik.ie).

BOSTIK HOTLINE

Smart help +353 1 8624998



FM 01696  
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin. Ireland. Tel: +353 1 8624900 [www.bostik.ie](http://www.bostik.ie)

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 01 8624999	Fax: 01 8402186	<a href="mailto:orders.bostik-irl@bostik.com">orders.bostik-irl@bostik.com</a>
Technical Advice	Tel: 01 8624998	Fax: 01 8402186	
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01 8624900	Fax: 01 8402186	



FM 01696  
BS EN ISO 9001:2008