

---

## **EVO-STIK FIRE CEMENT 1200**

### **HIGH TEMPERATURE RESISTANT SEALANT**

---

Evo-Stik Fire Sealant 1200 is a paste like product that will cure by drying to a hard and high temperature resistant seal.

#### **USES**

Sealing joints in heaters, open fire places and ovens. Gluing and joining temperature resistant stones.

#### **METHOD OF USE**

Surfaces must be clean, dry and dust free.

#### **APPLICATION**

Surfaces must be clean and free of dust and grease. Very porous surfaces should be slightly moistened. Finish with neutral soapy water.

Slowly heating after curing (after 48 hours) prevents air bubbles.

#### **FINISHING**

Tool off within minutes using a spatula or stick wetted with soapy water. It is the user's responsibility to dispose of all packaging correctly

#### **SPECIFICATION**

<b>TECHNICAL DATA</b>	<b>Unit</b>	<b>EVO-STIK FIRE CEMENT</b>
Basis		Sodium silicate
Application Temperature	°C	+15/ +40
Density	g/ ml	2.0
Solids	%	80
Open time	min	5-10
Drying time	hour	24-96
Joint movement capability	%	Nil
Frost resistant during transport		Yes
Temperature resistance after cure	° C	1200

#### **COLOURS**

Black

#### **QUANTITY ESTIMATOR**

Width x depth of joint x length (in linear metres) of joint, divide this by the volume of tube in ml = number of cartridges required. Typically 6mm x6 mm joint = 11 linear metres per cartridge

#### **LIMITATIONS**

Among others not recommended for expansion joints. Not waterproof.



# PRODUCT DATA

Date: 24 May 2010

Information Sheet No.: TDS01607

## LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as we cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability of use.

## SHELF LIFE & STORAGE

9 months under normal conditions. Protect from frost. Store in cool dry place.

## HEALTH & SAFETY

Please refer to MSDS prior to use. Under normal conditions of use the product is safe is non-hazardous. Wear suitable personal protective equipment. Keep out of reach of children. Do not take internally. Dispose of empty packaging correctly.

## PACKAGING

Product is supplied 310ml cartridges. 12 cartridges per box.

Sales & Technical contacts at Bostik	Telephone	Facsimile	Email addresses
Sales	01 8624999	01 8404427	<a href="mailto:orders.bostik-irl@bostik.com">orders.bostik-irl@bostik.com</a>
Technical Advice, Data & COSHH (MSDS) sheets	01 8624998	01 8402186	<a href="mailto:technical.ireland@bostik.com">technical.ireland@bostik.com</a>

This Product Data Sheet covers just one of a large range of products supplied by Bostik Industries Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Industries Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.