



Cementone PVA

BUILDING ADHESIVE, PRIMER & SEALER

Date: 17 October 2017

Fact Sheet No.: TDS00230

YOUR SMART ADVANTAGES

- Improves adhesion and bond strength
- For plastering, rendering, bonding, sealing and dustproofing
- Suitable for interior use

USES

Bostik PVA (formerly known as Cementone Rendabond PVA) is ready to use and is suitable for a wide range of building jobs. It is a highly effective primer, bonding agent, dustproofing agent and may also be used as an adhesive. It is economical and suitable for interior use in dry service conditions. For damp or external situations use Bostik SBR.

Bostik PVA can be used as a primer to improve adhesion to porous or difficult surfaces prior to plastering.

Bostik PVA can be used as a sealer to reduce dusting of concrete and plaster surfaces.

Bostik PVA bonds most building materials, provided one of the surfaces has a degree of porosity e.g. timber, plywood, blockboard, chipboard, fibreboard, expanded polystyrene, polyurethane foam, insulating board, brick, concrete, stone, and slate.

PRODUCT CHARACTERISTICS

Colour	White, dries to a transparent film
Form	Liquid
Specific Gravity	1.05 approx.
Composition	Polyvinyl acetate emulsion
Product Code	30812545 1 litre x 6 30812498 2.5 litre x 6

	30812497 5 litre x 4 30812537 25 litre
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 18 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +25°C
Coverage (undiluted)	6 – 14m ² per litre depending on application thickness and substrate
Open Time	5 to 10 minutes*
Tack Duration	10 to 90 minutes*
Bonding	Maximum strength is attained in 24 hours*
Priming	Dries after approx. 1 hour*
Sealing Concrete Floors	Leave to dry completely (usually 8 hours*), before allowing foot traffic
Solvent for Cleaning	Warm soapy water

* depending on temperature, humidity, coating weight and substrate

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik PVA refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Surfaces must be sound, dry, clean, and free from grease, dust or loose material.
2. Shake well before use.
3. Bostik PVA can be applied by brush, roller, spreader or from a squeezable plastic bottle.
4. Bonding work must be done when the adhesive is still wet or tacky, but when using as a primer Bostik PVA must be allowed to dry.

APPLICATION:

Primer

Porous Surfaces e.g. clay brick, sand-cement renders, cement sheet etc.

5. Dilute 1 part Bostik PVA to 5 parts water by volume. Apply to the surface and allow to dry.

Non-Porous Interior Surfaces e.g. engineering brick, glazed tiles and sound oil painted surfaces.

6. Apply Bostik PVA undiluted.

Plastering

Preparation

7. Ensure the surface to be plastered is clean, sound & dry and can support the weight of new plaster. Any loose or flaking material must be removed before applying PVA or plaster. Do not apply PVA over loose paint or any wallpaper.

To Bond New Plaster to Porous Surfaces e.g. brickwork, old plaster and timber)

8. Prime the surface with 1 part Bostik PVA to 5 parts water. When dry, coat the surface with a mixture of 3 parts Bostik PVA to 1 part water and while still wet or tacky apply the plaster.

To Bond New Plaster to Non-Porous Surfaces e.g. glazed tiles

9. Apply an undiluted coat of Bostik PVA and while still wet or tacky apply the plaster.

Bonding Agent

Interior Cement Render:

Dry Porous Interior Surfaces: for rendering onto pre-cast concrete, brick and other backings of a highly porous nature.

10. Prime and allow to dry as specified above.
11. Once priming coat has dried apply a bonding coat of 3 parts Bostik PVA to 1 part water by volume.
12. Allow film to develop tack.
13. Apply render in coats no greater than 10 mm thick to a maximum of 16 mm thickness.

Non-Porous Interior Surfaces:

14. Apply undiluted Bostik PVA as a bonding coat; apply plaster while it is still wet or tacky.

Dust Sealer

For sealing dusty surfaces - e.g. interior concrete.

15. Dilute 1 part Bostik PVA to 5 parts water by volume.

16. Apply 1 or 2 coats to the surface.

Adhesive

To Bond most Types of Wood Under Dry Conditions:

17. Apply undiluted Bostik PVA to one surface. Join surfaces immediately and apply weight or clamp joint for at least 1 hour.
18. Under normal conditions, joints can be handled carefully after 1 hour, although setting times may vary depending on the surface porosity and ambient conditions.
19. Full bond strength is normally obtained in 24 hours.
20. To obtain a longer open time (above method is usually 10 minutes), prime with a mixture of 1 part Bostik PVA to 5 parts water by volume. When the priming coat is dry apply the adhesive coat.

CLEANING

21. Clean tools and equipment immediately after use with warm soapy water before Bostik PVA has dried.

PRECAUTIONS IN USE

For damp or external situations use Bostik SBR. Bostik PVA should not be used in areas subject to frequent wetting. Do not apply below 5°C. For internal use only in dry service conditions. Bostik PVA can be used as a primer before painting when used according to paint manufacturers recommendations and instructions. Bostik PVA should not be used for rendered surfaces subject to constant immersion in water e.g. swimming pools. The product is not designed to harden concrete floors. The product will not bond two non-porous surfaces – in such cases, use an appropriate contact adhesive. Bostik PVA is not suitable for structural bonding or continuous load bearing applications.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik PVA, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com