



**Declaration of Performance** 

DOP -

EU\_31\_NRB

REVISION A

Product Type Notch Head, Bright Ring Shank Timber Nails

2. Identification As Defined

3. Intended Use For Structural Timber Products

4. Manufacturer Stanley Black & Decker bvba; Kanaalweg 112 IZ Ravenshout Zone 3, 3980 Tessenderlo, Belgium

5. Representative n/a

6. Assessment and Verification of Constancy of Performance 3

7., 8. Technical Specifications & Notified Bodies

Task Performed	Performed By	NB#	System of Assessment	Report	EN Standard
Initial Type Testing	КІТ	0769	3	70-100	EN14592:2008+A1:2012
Factory Production Control	Stanley Black & Decker	-	3	-	-

9. Declared Performance

1.

## **Dimensions**

Diameter - d 3 mm Profile Length - Lg > 4.5d Head Area - Ah 34.4 mm<sup>2</sup> Point Length - Lp  $0.5d \le Lp \le 2.5d$  Length - L 70-100 mm Coated Length - Lcoat > 0.5L

<u>Durability</u>		Harmonized Technical Specification
Material	Non-alloy steel	EN14592:2008+A1:2012 - Clause 6.1.2 in accordance with EN10016-2
Tensile Strength	Minimum 700 N/mm²	EN14592:2008+A1:2012 - Clause 6.1.2 in accordance with EN10218-1
Corrosion Protection	Service Class 1: Bright	EN14592:2008+A1:2012 - Clause 6.1.5 in accordance with EN1995-1-1

## Mechanical Strength and Stiffness

Yield Moment	$M_{y,k} = 2.97  \text{Nm}$	EN14592:2008+A1:2012 - Clause 6.1.4.2		
	172 y,k — 2.07 Mil	Tested to EN 409		
Withdrawal Parameter	f - 700 N/ 2	EN14592:2008+A1:2012 Clause 6.1.4.3		
in timber of characteristic density 350 kg/m³	$T_{ax,k} = 7.68 \text{N/mm}^2$	Tested to EN 1382		
With coating NONE				
Head Pull Through Parameter	f = 40.4 N/mm²	EN14592:2008+A1:2012 Clause 6.1.4.4.		
in timber of characteristic density 350 kg/m³	$T_{head,k} = 18.1 \text{N/mm}^2$	Tested to EN 1383		
Tensile Capacity	$f_{\text{cons},k} = 4.87 \text{kN}$	EN14592:2008+A1:2012 Clause 6.1.4.5.		
	r tens,k	Tested to EN 1383		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Colin Earl (VP HTF CDIY Europe)

(Diegem, Belgium, 06/05/2013)

Richard Waterman (Sr. Project Engineer)

(Rhode Island, USA, 06/05/2013)

Form: Rev A