

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Supercedes Date: 02-Mar-2018

Revision Date 02-Mar-2018 Revision Number 1

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement. Building and construction work.

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900

Tel: +353 (1) 8624900 Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Cement Portland White



Signal Word DANGER

Hazard statements

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Supercedes Date: 02-Mar-2018

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P261 - Avoid breathing dust

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P271 - Use only outdoors or in a well-ventilated area

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P315 - Get immediate medical advice/attention

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P501 - Dispose of contents/containers in accordance with local regulations

Additional information

Chromium VI reduced (according to Regulation (EC) 1907/2006 - Annex XVII)

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight)

2.3. Other Hazards

General Hazards

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Cement Portland White	266-043-4	65997-15-1	>25 - <40	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		Exempt
Calcium sulfate	231-900-3	7778-18-9	1 - <5	^		01-2119444918-26 -XXXX
Aluminum oxide (Al2O3)	215-691-6	1344-28-1	1 - <5	^		01-2119529248-35 -XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

Supercedes Date: 02-Mar-2018

General Advice If symptoms persist, call a doctor.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation

persists, call a doctor. Brush off loose particles from skin.

Eye contact If symptoms persist, call a doctor. In case of eye contact, remove contact lens and rinse

immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Ingestion Do NOT induce vomiting. Rinse mouth. If swallowed, seek medical advice immediately

and show this container or label.

Self-Protection of the First Aider Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsMay cause sensitisation of susceptible persons. Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire.

Unsuitable Extinguishing Media

None known

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating and toxic gases and vapours.

Hazardous Combustion Products Carbon oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid creating dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing and eye/face protection.

For emergency responders

Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent dust cloud. Take up mechanically, placing in appropriate containers for disposal.

Methods for cleaning up Avoid creating dust. Sweep up and shovel into suitable containers for disposal.

6.4. Reference to other sections

Supercedes Date: 02-Mar-2018

Reference to other sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Avoid contact with skin and eyes. Wash contaminated clothing before reuse.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep out of the reach of children. Protect from direct contact with water or excessive moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

Other Information

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Cement Portland White	-	TWA: 1 mg/m ³	STEL: 30 mg/m ³
65997-15-1		STEL: 3 mg/m ³	STEL: 12 mg/m ³
		_	TWA: 10 mg/m³ (inhalable)
			TWA: 4 mg/m³ (respirable)
Calcium sulfate	-	TWA: 10 mg/m ³	-
7778-18-9		STEL: 30 mg/m ³	
Aluminum oxide (Al2O3)	-	TWA: 10 mg/m ³	TWA: 10 mg/m³ inhalable dust
1344-28-1		TWA: 4 mg/m ³	TWA: 4 mg/m³ respirable dust
		STEL: 30 mg/m ³	
		STEL: 12 mg/m ³	

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Supercedes Date: 02-Mar-2018

Respiratory Protection

Eye/Face Protection Tight sealing safety goggles. Face protection shield. Wear safety glasses with side

shields (or goggles).

Hand Protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly

Revision Date 02-Mar-2018

Revision Number 1

and if there is any sign of damage to the glove material.

Skin and Body Protection Suitable protective clothing. Gloves made of plastic or rubber. Avoid contact with skin,

eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact. No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid

Remarks • Method

generation of dust.

Recommended filter type: Particle filter device (DIN EN 143).

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical StateSolidAppearancePowderColourOff-whiteOdourSlight

Odour Threshold No information available

<u>Property</u> <u>Values</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash Point No information available
Evaporation Rate No information available
Flammability (solid, gas)
No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit

Vapour Pressure

Vapour Density

Relative Density

No information available
No information available
No information available
No information available

Water Solubility Cement based products react and

solidify in contact with water No information available

Solubility in Other Solvents **Partition Coefficient** No information available **Autoignition Temperature** No information available No information available **Decomposition Temperature** No information available **Explosive Properties Explosive Limits** No information available No information available Upper No information available Lower No information available **Oxidising Properties Kinematic Viscosity** No information available

Dynamic Viscosity No information available

9.2. Other information

Softening Point
Molecular Weight
Solvent content (%)

No information available
No information available
No information available

Solid content (%)

Density No data available Bulk Density No data available

VOC content (%)

Section 10: STABILITY AND REACTIVITY

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Supercedes Date: 02-Mar-2018

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

Inhalation Inhalation of dust in high concentration may cause irritation of respiratory system. Eve contact Severely irritating to eyes. Dust contact with the eyes can lead to mechanical irritation. **Skin Contact** When cement reacts with water a strong alkaline solution is produced. Prolonged

contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Ingestion Based on available data, the classification criteria are not met.

Sensitisation Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a

reduction agent (related to the total dry weight).

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation When cement reacts with water a strong alkaline solution is produced. Prolonged

contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Serious eye damage/eye irritation Risk of serious damage to eyes.

May cause sensitisation of susceptible persons. Cement product for which the amount of Sensitisation

chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry

weight).

Germ Cell Mutagenicity Not applicable.

Carcinogenicity Not applicable. Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Reproductive Toxicity No information available.

STOT - Single Exposure May cause disorder and damage to the. Respiratory system.

STOT - Repeated Exposure No information available.

Target Organ Effects Eyes, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity

Supercedes Date: 02-Mar-2018

Acute Toxicity

Component Information

Toxicity Data Data obtained on the component(s) include

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity No information available

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Calcium sulfate	CL50 (72h) >100 mg/L Algae	LC50 96 h > 1970 mg/L	CE50 (48h) >100 mg/L	
7778-18-9		(Pimephales promelas static)	Waterflea (Daphnia magna)	
		LC50 96 h = 2980 mg/L		
		(Lepomis macrochirus static)		

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Supercedes Date: 02-Mar-2018

Waste from Residues/Unused

Products

Disposal should be in accordance with applicable regional, national and local laws and

Revision Date 02-Mar-2018

Revision Number 1

regulations.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

Other Information Waste codes should be assigned by the user based on the application for which the

product was used.

Section 14: TRANSPORTATION INFORMATION

ADR

14.1 UN/ID noNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated14.5 Environmental HazardNot applicable

14.6 Special Provisions None

<u>IMDG</u>

14.1 UN NumberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated14.5 Marine PollutantNp14.6 Special ProvisionsNone

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

<u>RID</u>

14.1UN NumberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing GroupNot regulated14.5Environmental HazardNot applicable14.6Special ProvisionsNone

ICAO (air)

14.1UN/ID noNot regulated14.2Proper Shipping NameNot regulated14.3Hazard ClassNot regulated14.4Packing GroupNot regulated14.5Environmental HazardNot applicable14.6Special ProvisionsNone

IATA

14.1 UN/ID no
Not regulated
Not applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

•

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Supercedes Date: 02-Mar-2018

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

None

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H335 - May cause respiratory irritation

H315 - Causes skin irritation

H318 - Causes serious eye damage

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls and personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT (RE): Specific target organ toxicity - Repeated exposure STOT (SE): Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Revision Date 02-Mar-2018

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM IVORY

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 02-Mar-2018

Key literature references and sources for data

Indication of changes

Supercedes Date: 02-Mar-2018

Revision Note Not applicable.

Training Advice No information available

Further information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision Date 02-Mar-2018