

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name EVO-STIK SILICONE SEAL MP WHITE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Head office
Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word

None

Hazard statements

Not classified

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children

2.3. Other Hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

PBT and vPvB assessment

This preparation contains substances considered to be very persistent and very bio-accumulating (vPvB), or to be very persistent or very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

| Chemical name | EC No. | CAS No. | Weight-% | Classification according to Regulation (EC) No. 1272/2008 [CLP] | Specific concentration limit (SCL) | REACH Registration Number |
|--|-----------|------------|-------------|---|------------------------------------|---------------------------|
| Distillates, petroleum, hydrotreated middle | 265-148-2 | 64742-46-7 | >25 - <40 | Asp. Tox. 1 (H304) | | 01-2119827000-58-XXXX |
| Petroleum distillates, hydrotreated light | 265-149-8 | 64742-47-8 | 5 - <10 | Asp. Tox. 1 (H304) (EUH066) | | 01-2119484819-18-XXXX |
| Dodecamethylcyclhexasiloxane | 208-762-8 | 540-97-6 | 0.1 - <1 | PBT vPvB | | 01-2119517435-42-XXXX |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] | 264-843-8 | 64359-81-5 | 0.01 - <0.1 | Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (410) M=10 | | No data available |

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

| Chemical name | EC No. | CAS No. | SVHC candidates |
|------------------------------|-----------|----------|-----------------|
| Dodecamethylcyclhexasiloxane | 208-762-8 | 540-97-6 | X |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|-----------------------|---|
| General advice | Take a copy of the Safety Data Sheet when going for medical treatment. |
| Inhalation | Remove to fresh air. IF exposed or concerned: Get medical advice/attention. |
| Eye contact | Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor. |

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supercedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

| | |
|---------------------|---|
| Skin contact | Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor. |
| Ingestion | Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------|---------------------------|
| Symptoms | No information available. |
|-----------------|---------------------------|

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|------------------------|------------------------|
| Note to doctors | Treat symptomatically. |
|------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|-------------------------------------|---|
| Suitable extinguishing media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
|-------------------------------------|---|

| | |
|---------------------------------------|---|
| Unsuitable extinguishing media | Full water jet. Do not scatter spilled material with high pressure water streams. |
|---------------------------------------|---|

5.2. Special hazards arising from the substance or mixture

| | |
|---|---|
| Specific hazards arising from the chemical | Thermal decomposition can lead to release of toxic and corrosive gases/vapours. |
|---|---|

| | |
|--------------------------------------|---|
| Hazardous combustion products | Carbon monoxide. Carbon dioxide (CO ₂). |
|--------------------------------------|---|

5.3. Advice for firefighters

| | |
|---|--|
| Special protective equipment for fire-fighters | Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. |
|---|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|---|
| Personal precautions | Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. |
|-----------------------------|---|

| | |
|--------------------------|---|
| Other information | Ventilate the area. Prevent further leakage or spillage if safe to do so. |
|--------------------------|---|

| | |
|---------------------------------|---|
| For emergency responders | Use personal protection recommended in Section 8. |
|---------------------------------|---|

6.2. Environmental precautions

| | |
|----------------------------------|--|
| Environmental precautions | Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information. |
|----------------------------------|--|

6.3. Methods and material for containment and cleaning up

| | |
|--------------------------------|--|
| Methods for containment | Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. |
|--------------------------------|--|

| | |
|--------------------------------|---|
| Methods for cleaning up | Take up mechanically, placing in appropriate containers for disposal. |
|--------------------------------|---|

6.4. Reference to other sections

| | |
|------------------------------------|--|
| Reference to other sections | See section 8 for more information. See section 13 for more information. |
|------------------------------------|--|

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific Use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Distillates, petroleum, hydrotreated middle (64742-46-7)

| | |
|--------------------------------|--|
| Type | worker Long term Systemic health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 16.4 mg/m ³ |

| | |
|--------------------------------|---|
| Type | worker Short term Systemic health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 5.003 mg/m ³ |

| | |
|--------------------------------|--|
| Type | worker Long term Systemic health effects |
| Exposure route | Dermal |
| Derived No Effect Level (DNEL) | 2.9 mg/kg bw/d |

Petroleum distillates, hydrotreated light (64742-47-8)

Dodecamethylcyclohexasiloxane (540-97-6)

| | |
|--------------------------------|--|
| Type | worker Long term Systemic health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 11 mg/m ³ |

| | |
|----------------|---------------------------------------|
| Type | worker Long term Local health effects |
| Exposure route | Inhalation |

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

| | |
|--------------------------------|--|
| Derived No Effect Level (DNEL) | 1.22 mg/m ³ |
| Type | worker Short term Local health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 6.1 mg/m ³ |

| | |
|---|--|
| Derived No Effect Level (DNEL) | |
| Distillates, petroleum, hydrotreated middle (64742-46-7) | |
| Type | Consumer Long term Systemic health effects |
| Exposure route | Oral |
| Derived No Effect Level (DNEL) | 1.3 mg/kg bw/d |

| | |
|---|--|
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| Type | Consumer Long term Systemic health effects |
| Exposure route | Oral |
| Derived No Effect Level (DNEL) | 19 mg/kg bw/d |

| | |
|--|--|
| Dodecamethylcyclhexasiloxane (540-97-6) | |
| Type | Consumer Long term Systemic health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 2.7 mg/m ³ |

| | |
|--------------------------------|---|
| Type | Consumer Long term Local health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 0.3 mg/m ³ |

| | |
|--------------------------------|--|
| Type | Consumer Short term Local health effects |
| Exposure route | Inhalation |
| Derived No Effect Level (DNEL) | 1.5 mg/m ³ |

| | |
|--------------------------------|--|
| Type | Consumer Long term Systemic health effects |
| Exposure route | Oral |
| Derived No Effect Level (DNEL) | 1.7 mg/kg bw/d |

| | |
|--------------------------------|---|
| Type | Consumer Short term Systemic health effects |
| Exposure route | Oral |
| Derived No Effect Level (DNEL) | 1.7 mg/kg bw/d |

Predicted No Effect Concentration (PNEC) No information available.

| | |
|---|--|
| Predicted No Effect Concentration (PNEC) | |
| Dodecamethylcyclhexasiloxane (540-97-6) | |
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Sewage treatment plant | >1 mg/l |
| Freshwater sediment | 13 mg/kg dry weight |
| Marine sediment | 1.3 mg/kg dry weight |
| Soil | 3.77 mg/kg dry weight |

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

Skin and body protection
Respiratory protection

information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Suitable protective clothing.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|--------------------------|
| Physical state | Liquid |
| Appearance | Paste |
| Colour | White |
| Odour | Acetic acid |
| Odour threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--|------------------------------|-------------------------|
| pH | No data available | |
| Melting point / freezing point | No data available | |
| Boiling point / boiling range | No data available | |
| Flash point | > 100 °C | |
| Evaporation rate | No data available | |
| Flammability (solid, gas) | Not applicable for liquids . | |
| Flammability Limit in Air | | |
| Upper flammability or explosive limits | No data available | |
| Lower flammability or explosive limits | No data available | |
| Vapour pressure | No data available | |
| Vapour density | No data available | |
| Relative density | 0.9 - 1.0 | |
| Water solubility | Negligible | |
| Solubility(ies) | No data available | |
| Partition coefficient | No data available | |
| Autoignition temperature | 210 °C | |
| Decomposition temperature | No data available | |
| Kinematic viscosity | > 21 mm ² /s | @ 40°C |
| Dynamic viscosity | No data available | |
| Explosive properties | No data available | |
| Oxidising properties | No data available | |

9.2. Other information

| | |
|-------------------|-----------------------------|
| Solid content (%) | No information available |
| Softening Point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | approx. 0 g/L / 0 % |
| Density | 0.9 - 1.0 g/cm ³ |
| Bulk density | No information available |

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supercedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 7,919.30 mg/kg

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|----------------------|--------------------------------------|------------------------|
| Distillates, petroleum, hydrotreated middle 64742-46-7 | =7400 mg/kg (Rattus) | > 2000 mg/kg (Oryctolagus cuniculus) | =4.6 mg/L (Rattus) 4 h |
| Petroleum distillates, hydrotreated light 64742-47-8 | >5000 mg/kg (Rattus) | > 2000 mg/kg (Oryctolagus cuniculus) | >5.2 mg/L (Rattus) 4 h |
| Dodecamethylcyclohexasiloxane | >50 g/kg (Rattus) | | |

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
 Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
 Revision Number 2

| | | | |
|--|----------------------|--------------------------------------|-------------------------|
| 540-97-6 | | | |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5 | =1636 mg/kg (Rattus) | > 2000 mg/kg (Oryctolagus cuniculus) | =0.26 mg/L (Rattus) 4 h |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

| Component Information | | | |
|---|------------|----------------|-------------|
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5) | | | |
| Method | Species | Exposure route | Results |
| OECD Test No. 406: Skin Sensitisation | Guinea pig | | sensitising |

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to Micro-organisms | Crustacea | M-Factor |
|--|--|--|-----------------------------|---|----------|
| Distillates, petroleum, hydrotreated middle 64742-46-7 | EL50, Skeletonema costatum, 72hr, > 10 000 mg/l, | LC50 96 h = 35 mg/L (Pimephales promelas flow-through) LC50 96 h > 10000 mg/L (Pimephales promelas static) | - | LL50, Acartia tonsa, 48 Hr, > 3 193 mg/l, | - |
| Petroleum distillates, hydrotreated light 64742-47-8 | - | LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss) LC50: =45mg/L (96h, Pimephales | - | LC50: =4720mg/L (96h, Den-dronereides heteropoda) | - |

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

| | | | | | |
|--|---|--|---|---|-----------------------------|
| | | promelas) | | | |
| Dodecamethylcyclohexasiloxane 540-97-6 | - | 90 d NOEC ≥14 µg/L, Oncorhynchus mykiss | - | NOEC ≥4.6 µg/L (21d) OECD 211 Daphnia Magna | - |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5 | EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OEC D 201) | LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss)(OECD 203) | - | EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202) | Acute M=100 Chronic M=10 |

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

| Method | Exposure time | Value | Results |
|---|---------------|-----------|--------------|
| OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems | | Half-life | 1.1-1.3 days |

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient | Bioconcentration factor (BCF) |
|--|-----------------------|-------------------------------|
| Petroleum distillates, hydrotreated light 64742-47-8 | - | 159 |
| Dodecamethylcyclohexasiloxane 540-97-6 | 8.87 | - |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5 | 4.4 | 13 |

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This preparation contains substances considered to be very persistent and very bio-accumulating (vPvB), or to be very persistent or very bioaccumulating (vPvB).

| Chemical name | PBT and vPvB assessment |
|--|--|
| Distillates, petroleum, hydrotreated middle 64742-46-7 | The substance is not PBT / vPvB PBT assessment does not apply |
| Petroleum distillates, hydrotreated light 64742-47-8 | The substance is not PBT / vPvB |
| Dodecamethylcyclohexasiloxane 540-97-6 | PBT / vPvB substance |
| 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5 | The substance is not PBT / vPvB |

12.6. Other adverse effects

Other adverse effects No information available.

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|--|
| Waste from residues/unused products | Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. |
| Contaminated packaging | Do not reuse empty containers. Handle contaminated packages in the same way as the product itself. |
| European Waste Catalogue | 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09 |
| Other information | Waste codes should be assigned by the user based on the application for which the product was used. |

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|---------------------------------|----------------|
| 14.1 UN Number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing Group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

IMDG

| | |
|---|--------------------------|
| 14.1 UN number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Marine Pollutant | Np |
| 14.6 Special Provisions | None |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | No information available |

Air transport (ICAO-TI / IATA-DGR)

| | |
|---------------------------------|----------------|
| 14.1 UN number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

| Chemical name | CAS No. |
|-------------------------------|----------|
| Dodecamethylcyclohexasiloxane | 540-97-6 |

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supercedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

28 . The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). This note applies only to certain complex coal and oil-derived substances in Annex I. Mineral oils are known to cause cancer because of carcinogenic components (e.g. benzene). The mineral oil in this product is highly refined and should not be considered a carcinogen.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H400 - Very toxic to aquatic life

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

| | | | |
|---------|--|------|----------------------------------|
| TWA | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value | * | Skin designation |
| PBT | Persistent, Bioaccumulative, and Toxic (PBT) Chemicals | | |
| STOT RE | Specific target organ toxicity - Repeated exposure | | |
| STOT SE | Specific target organ toxicity - Single exposure | | |
| EWC: | European Waste Catalogue | | |

Key literature references and sources for data

No information available

Prepared By

Product Safety & Regulatory Affairs

SAFETY DATA SHEET

EVO-STIK SILICONE SEAL MP WHITE
Supersedes Date: 05-Apr-2016

Revision date 30-Sep-2019
Revision Number 2

Revision date 30-Sep-2019

Indication of changes

Revision note SDS sections updated: 1, 3, 11, 12.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet