

SEALCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name SEALCRETE LINE MARKING PAINT BLUE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Industries Limited
Newtown, Swords
Co. Dublin Ireland
Tel: +353 (1) 8624900
Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 3 - (H412)
aerosols	Category 1 - (H222, H229)

2.2. Label Elements

Contains: Acetone, Solvent naphtha, petroleum, light aromatic, n-Butyl acetate, Benzene, 1,2,4-trimethyl-



Signal word
Danger

Hazard statements

H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P405 - Store locked up.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	270-704-2	68476-85-7	>25 - <40	Flam. Gas 1 (H220) Press. Gas (H280)		--
Acetone	200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330-49-XXXX
Solvent naphtha, petroleum, light aromatic	265-199-0	64742-95-6	5 - <10	STOT SE 3 (H335) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) (EUH066) Flam. Liq. 2 (H225)		01-2119486773-24-XXXX

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
 Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
 Revision Number 2

Titanium dioxide	236-675-5	13463-67-7	1 - <5	Carc. 2 (H351i)		01-2119489379-17-XXXX
n-Butyl acetate	204-658-1	123-86-4	1 - <5	(EUH066) STOT SE 3 (H336) Flam. Liq. 3 (H226)		01-2119485493-29-XXXX
Benzene, 1,2,4-trimethyl-	202-436-9	95-63-6	1 - <5	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226)		01-2119472135-42-XXXX
Cumene	202-704-5	98-82-8	0.1 - <1	STOT SE 3 (H335) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226)		--
1,3,5-Trimethylbenzene	203-604-4	108-67-8	0.1 - <1	STOT SE 3 (H335) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226)	STOT SE 3 :: C>=25%	01-2119463878-19-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	IF exposed or concerned: Get medical advice/attention. Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supercedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
 Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
 Revision Number 2

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific Use(s)
 Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	-	-	TWA: 1000 ppm TWA: 1750 mg/m ³ STEL: 1250 ppm STEL: 2180 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	-	TWA: 25 ppm 120 mg/m ³
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
n-Butyl acetate 123-86-4	TWA: 50 ppm TWA: 241 mg/m ³ STEL: 150 ppm STEL: 723 mg/m ³	TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 150 ppm TWA: 724 mg/m ³ STEL: 200 ppm STEL: 966 mg/m ³
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 20 ppm TWA: 100 mg/m ³	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 60 ppm STEL: 300 mg/m ³	-
Cumene 98-82-8	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 50 ppm STEL: 250 mg/m ³ * TWA: 50 mg/m ³ during exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 50 ppm STEL: 250 mg/m ³ Sk*	TWA: 25 ppm TWA: 125 mg/m ³ STEL: 50 ppm STEL: 250 mg/m ³ Sk*

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

	Occupational Exposure Limits for Chemicals Agents (SCOEL) TWA: 10 ppm during exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL) STEL: 250 mg/m ³ during exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL) STEL: 50 ppm during exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL) * during exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL)		
1,3,5-Trimethylbenzene 108-67-8	TWA: 20 ppm TWA: 100 mg/m ³	TWA: 20 ppm TWA: 100 mg/m ³ STEL: 60 ppm STEL: 300 mg/m ³	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	
n-Butyl acetate (123-86-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	300 mg/m ³	

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

worker Short term Systemic health effects	Inhalation	600 mg/m ³	
worker Long term Local health effects	Inhalation	300 mg/m ³	
worker Short term Local health effects	Inhalation	600 mg/m ³	
worker Long term Systemic health effects	Dermal	11 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

n-Butyl acetate (123-86-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	300 mg/m ³	
Consumer Long term Local health effects	Inhalation	35.7 mg/m ³	
Consumer Short term Local health effects	Inhalation	300 mg/m ³	
Consumer Long term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	6 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	2 mg/kg bw/d	

SAFETY DATA SHEET

SEALCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Predicted No Effect Concentration (PNEC) No information available.
(PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

n-Butyl acetate (123-86-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.18 mg/l
Marine water	0.018 mg/l
Freshwater - intermittent	0.36 mg/l
Sewage treatment plant	35.6 mg/l
Freshwater sediment	0.981 mg/l
Marine sediment	0.0981 mg/l
Soil	0.0903 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Aerosol
Appearance Aerosol
Colour Blue
Odour Solvent

SAFETY DATA SHEET

SEALCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Odour threshold	No information available	
Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	Not applicable, Aerosol	Not applicable, Aerosol
Flash point	Not applicable, Aerosol	Not applicable, Aerosol
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	9.5	
Lower flammability or explosive limits	1.8	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	410 °C	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	690 g/L
Density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Hazardous decomposition products None under normal use conditions. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause irritation. Prolonged contact may cause redness and irritation. Specific test data for the substance or mixture is not available. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal)	15,700.00 mg/kg
ATEmix (inhalation-dust/mist)	27.40 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	=8400 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=3400 ppm (Rattus) 4 h
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
n-Butyl acetate 123-86-4	>10650 mg/kg (Rattus)	> 17600 mg/kg (Oryctolagus cuniculus)	=390 ppm (Rattus) 4 h
Benzene, 1,2,4-trimethyl- 95-63-6	=3280 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=18 g/m ³ (Rattus) 4 h
Cumene 98-82-8	=1400 mg/kg (Rattus)	= 12300 µL/kg (Oryctolagus cuniculus)	=39000 mg/m ³ (Rattus) 4 h > 3577 ppm (Rattus) 6 h
1,3,5-Trimethylbenzene 108-67-8	=5000 mg/kg (Rattus)		= 24 g/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
 Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
 Revision Number 2

Component Information					
Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion					Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50 48 h = 3.2 mg/L (Daphnia magna)		

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
n-Butyl acetate 123-86-4	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50 96 h 17 - 19 mg/L (Pimephales promelas flow-through)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 48 h = 44 mg/L (Daphnia magna)		
Benzene, 1,2,4-trimethyl- 95-63-6	-	LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas)	-	EC50: =6.14mg/L (48h, Daphnia magna)		
Cumene 98-82-8	EC50: =2.6mg/L (72h, Pseudokirchneri ella subcapitata)	LC50: =2.7mg/L (96h, Oncorhynchus mykiss) LC50: 6.04 - 6.61mg/L (96h, Pimephales promelas) LC50: =5.1mg/L (96h, Poecilia reticulata) LC50: =4.8mg/L (96h, Oncorhynchus mykiss)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	EC50: 7.9 - 14.1mg/L (48h, Daphnia magna) EC50: =0.6mg/L (48h, Daphnia magna)		
1,3,5-Trimethylbenzene 108-67-8	-	LC50: =3.48mg/L (96h, Pimephales promelas)	-	EC50: =50mg/L (24h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Acetone (67-64-1)			
Method	Exposure time	Value	Results
	28 days	biodegradation	91 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	2.8	-
Acetone 67-64-1	-0.24	0.69
n-Butyl acetate 123-86-4	1.81	-
Benzene, 1,2,4-trimethyl- 95-63-6	3.63	-

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Cumene 98-82-8	3.7	35.5
-------------------	-----	------

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	The substance is not PBT / vPvB
Acetone 67-64-1	The substance is not PBT / vPvB
Solvent naphtha, petroleum, light aromatic 64742-95-6	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
n-Butyl acetate 123-86-4	The substance is not PBT / vPvB PBT assessment does not apply
Benzene, 1,2,4-trimethyl- 95-63-6	The substance is not PBT / vPvB PBT assessment does not apply
Cumene 98-82-8	The substance is not PBT / vPvB
1,3,5-Trimethylbenzene 108-67-8	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
Waste codes / waste designations according to EWC / AVV	16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 04 metallic packaging
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

SAFETY DATA SHEET

SEALOCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.2
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	327, 625, 344, 190
Classification code	5A
Tunnel restriction code	(E)
Limited Quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Marine pollutant	NP
14.6 Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A145, A167, A802
Limited Quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

SEALCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	50	200

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

SAFETY DATA SHEET

SEALCRETE LINE MARKING PAINT BLUE
Supersedes Date: 13-Oct-2017

Revision date 20-Jan-2021
Revision Number 2

vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Jan-2021

Indication of changes

Revision note SDS sections updated, 2, 3, 7, 15.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet