

Revision Date 24-Feb-2017

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY Product Name

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Adhesives. Recommended use None known Uses advised against

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900

Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

Unknown acute toxicity 39 % of the mixture consists of ingredient(s) of unknown toxicity

Unknown aquatic toxicity Contains 39 % of components with unknown hazards to the aquatic environment

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Cement, portland, chemicals



EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

Signal Word

DANGER

Hazard statements

H335 - May cause respiratory irritation

H315 - Causes skin irritation

H318 - Causes serious eye damage

H317 - May cause an allergic skin reaction

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P260 - Do not breathe dust

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P313 - Get medical advice/attention

P362 + P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

General Hazards

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	40 - <80	^		Exempt
Cement, portland, chemicals	266-043-4	65997-15-1	>25 - <40	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		No Data Available

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017

Version 1

Revision Date 24-Feb-2017

4.1. Description of first aid measures

General Advice If symptoms persist, call a doctor.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Skin Contact Brush off loose particles from skin. Wash off immediately with soap and plenty of water

while removing all contaminated clothes and shoes. If skin irritation persists, call a

doctor.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. If symptoms

persist, call a doctor.

Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. If Ingestion

swallowed, seek medical advice immediately and show this container or label.

Self-protection of the first aider Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of dust in high concentration may cause irritation of respiratory system. May

cause irritation of the mouth, throat and stomach. Irritating to skin. May cause redness,

itching, and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation of susceptible persons. Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire.

Unsuitable Extinguishing Media

None known

5.2. Special hazards arising from the substance or mixture

No information available.

Hazardous Combustion Products Carbon oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid creating dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing and eye/face protection.

For emergency responders

Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system.

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent dust cloud. Take up mechanically, placing in appropriate containers for disposal.

Methods for cleaning up Avoid creating dust. Sweep up and shovel into suitable containers for disposal.

6.4. Reference to other sections

Reference to other sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Avoid contact with skin and eyes. Wash contaminated clothing before reuse.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep out of the reach of children. Protect from direct contact with water or excessive moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3. Specific end use(s)

Other Information

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Quartz	=	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7		_	_
Cement, portland, chemicals	-	TWA: 4 mg/m ³	STEL: 30 mg/m ³
65997-15-1		TWA: 10 mg/m ³	STEL: 12 mg/m ³
		STEL: 30 mg/m ³	TWA: 10 mg/m ³
		STEL: 12 mg/m ³	TWA: 4 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield. Wear safety glasses with side

shields (or goggles).

Hand Protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Gloves made of plastic or rubber. Ensure that the breakthrough time of

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

the glove material is not exceeded. Refer to glove supplier for information on

breakthrough time for specific gloves. Gloves should be replaced regularly and if there is

Revision Date 24-Feb-2017

any sign of damage to the glove material.

Skin and Body Protection Suitable protective clothing. Apron. Gloves made of plastic or rubber. Avoid contact with

skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin

contact.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid

Remarks • Method

pH (as aqueous solution)

generation of dust.

Recommended Filter type: Particle filter device (DIN EN 143).

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical StateSolidAppearancePowderColourgreyOdourNegligible

Odour Threshold No information available

 Property
 Values

 pH
 11 - 14

Melting point/freezing point

Boiling Point

Flash Point

Evaporation Rate

Flammability (solid, gas)

No information available
No information available
No information available
No information available

Flammability Limit in Air

Upper Flammability Limit No information available Lower Flammability Limit No information available **Vapour Pressure** No information available **Vapour Density** No information available No information available **Specific Gravity Water Solubility** No information available **Solubility in Other Solvents** No information available **Partition Coefficient** No information available No information available **Autoignition Temperature Decomposition Temperature** No information available No information available **Explosive Properties Explosive Limits** No information available Upper No information available No information available Lower **Oxidising Properties** No information available **Kinematic Viscosity** No information available

Dynamic Viscosity No information available

9.2. Other information

Softening Point
Molecular Weight
Solvent content (%)
No information available
No information available
No information available

Solid content (%) 100

Density No Data Available
Bulk Density No Data Available

VOC content (%)

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

None under normal use conditions.

10.2. Chemical stability

Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

Inhalation Inhalation of dust in high concentration may cause irritation of respiratory system.

Eye contact Corrosive to the eyes and may cause severe damage including blindness.

Skin Contact

May cause skin irritation and/or dermatitis. When cement reacts with water a strong

alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in

wet cement even when wearing trousers.

IngestionNo Data Available.SensitisationNo Data Available.

Skin Corrosion/IrritationContact causes severe skin irritation and possible burns.

Serious eye damage/eye irritation Risk of serious damage to eyes.

Sensitisation Repeated or prolonged contact may cause allergic reactions in very susceptible persons.

Germ Cell Mutagenicity Not applicable.

Carcinogenicity Not applicable.

Reproductive Toxicity No information available.

STOT - Single Exposure May cause disorder and damage to the. Respiratory system.

STOT - Repeated Exposure No information available.

Target Organ Effects Eyes, Lungs, Respiratory system, Skin.

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017

Version 1

Revision Date 24-Feb-2017

Aspiration Hazard

No information available.

Numerical measures of toxicity

Acute Toxicity

Unknown acute toxicity 39 % of the mixture consists of ingredient(s) of unknown toxicity.

39 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

- 39 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
- 39 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
- 39 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapour).
- 39 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information

Toxicity Data Data obtained on the component(s) include

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Not considered to be harmful to aquatic life

Component Information

Data obtained on the component(s) include

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

No information available. Mobility in soil

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017

Version 1

Revision Date 24-Feb-2017

Waste from Residues/Unused

Products

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 **European Waste Catalogue**

01, 17 09 02 and 17 09 03

Other Information Waste codes should be assigned by the user based on the application for which the

product was used.

Section 14: TRANSPORTATION INFORMATION

ADR

14.1 UN/ID no Not regulated Not regulated 14.2 Proper Shipping Name 14.3 Hazard Class Not regulated Not regulated 14.4 Packing Group 14.5 Environmental Hazard Not applicable None

14.6 Special Provisions

IMDG

14.1 UN/ID no Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Hazard Class Not regulated 14.4 Packing Group Not regulated 14.5 Marine Pollutant Np

14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

RID

14.1 UN/ID no Not regulated Not regulated 14.2 Proper Shipping Name 14.3 Hazard Class Not regulated 14.4 Packing Group Not regulated 14.5 Environmental Hazard Not applicable

14.6 Special Provisions None

ICAO (air)

14.1 UN/ID no Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Hazard Class Not regulated 14.4 Packing Group Not regulated 14.5 Environmental Hazard Not applicable

14.6 Special Provisions None

IATA

14.1 UN/ID no Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Hazard Class Not regulated 14.4 Packing Group Not regulated 14.5 Environmental Hazard Not applicable 14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017 Version 1

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No	Restrictions on use
Cement, portland, chemicals	65997-15-1	47.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

None

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H335 - May cause respiratory irritation

H315 - Causes skin irritation

H318 - Causes serious eye damage

H317 - May cause an allergic skin reaction

Legend

SVHC: Substances of Very High Concern for Authorisation:

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT (RE): Specific target organ toxicity - Repeated exposure STOT (SE): Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

EVO-STIK TECHNIK RAPID SET FLEXIBLE GREY

Supercedes Date: 24-Feb-2017

Version 1

Revision Date 24-Feb-2017

Classification and labeling data calculated from data received from raw material suppliers

Product Safety & Regulatory Affairs **Prepared By**

Revision Date 24-Feb-2017

Indication of changes

Revision Note Not applicable.

No information available **Training Advice**

Additional information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet