

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 3 - (H226)

2.2. Label Elements

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)





Signal word WARNING

Hazard statements

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

H226 - Flammable liquid and vapour

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

·

EU Specific Hazard Statements

Supercedes Date: 29-Jan-2020

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand
- P102 Keep out of reach of children
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 Do not breathe vapour
- P273 Avoid release to the environment
- P280 Wear protective gloves and eye/face protection
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed
- P501 Dispose of contents/container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures 3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	919-006-8		10 - <20	Asp. Tox. 1 (H304) Aquatic Chronic 4 (H413) (EUH066)		01-2119455996- 19-xxxx
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	5 - <10	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)		01-2119458049- 33-XXXX
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides	263-087-6	61789-77-3	0.1 - <1	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Aquatic Acute 1 (H400)		No data available

Revision date 30-Jan-2020

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Revision date 30-Jan-2020 Supercedes Date: 29-Jan-2020 Revision Number 2.01

		Aquatic Chronic 2 (H410)	
			<u> </u>

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. **General advice**

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information.

4.2. Most important symptoms and effects, both acute and delayed

No information available. **Symptoms**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Dry chemical. Carbon dioxide (CO2). Alcohol resistant foam. Suitable extinguishing media

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be

inefficient. Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Carbon oxides. **Hazardous combustion products**

5.3. Advice for firefighters

Special protective equipment for Firefighters should wear self-contained breathing apparatus and full firefighting turnout

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020

gear. Use personal protection equipment. fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid Personal precautions

contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static

Revision date 30-Jan-2020

Revision Number 2.01

discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Dyke far ahead of spill: use dry sand to contain the flow of material. Absorb with earth.

sand or other non-combustible material and transfer to containers for later disposal.

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled Methods for cleaning up

containers. Take up mechanically, placing in appropriate containers for disposal.

Eliminate all ignition sources if safe to do so. Prevention of secondary hazards

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing Advice on safe handling

vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in

accordance with good industrial hygiene and safety practice.

Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when General hygiene considerations

using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

> heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

particular national regulations.

7.3. Specific end use(s)

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020

Specific Use(s)

Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

This product, as supplied, does not contain any hazardous materials with occupational **Exposure Limits**

exposure limits established by the region specific regulatory bodies

Chemical name	European Union	Ireland	United Kingdom
Limestone	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³	TWA: 4 mg/m ³
		STEL: 30 mg/m ³	STEL: 30 mg/m ³
		STEL: 12 mg/m ³	STEL: 12 mg/m ³
Isopropyl alcohol	-	TWA: 200 ppm	TWA: 400 ppm
67-63-0		STEL: 400 ppm	TWA: 999 mg/m ³
		Sk*	STEL: 500 ppm
			STEL: 1250 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	worker Long term Systemic health effects		
Exposure route	Inhalation		
Derived No Effect Level (DNEL)	330 mg/m³		

Туре	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	44 ma/ka bw/d

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Туре	Consumer Long term Systemic health effects		
Exposure route	Inhalation		
Derived No Effect Level (DNEL)	71 mg/m ³		

Туре	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Туре	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	26 mg/kg bw/d

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. **Engineering controls**

Revision date 30-Jan-2020

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

•

Personal Protective Equipment

Supercedes Date: 29-Jan-2020

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature. Recommended Use:. Polyvinyl chloride

Revision date 30-Jan-2020

Revision Number 2.01

(PVC).

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic

or rubber.

Respiratory protection In case of mist, spray or aerosol exposure wear suitable personal respiratory protection

and protective suit. In case of inadequate ventilation wear respiratory protection.

@ 40°C

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearancePasteColourBlackOdourSlight

Odour threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point > 39 °C
Evaporation rate
No data available
>= 153 °C
> 39 °C
No data available

Flammability (solid, gas) Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableVapour densityNo data availableRelative densityNo data availableWater solubilityInsoluble in waterSolubility(ies)No data availablePartition coefficientNo data available

Autoignition temperature 200 °C

Decomposition temperatureNo data available
Kinematic viscosity
No data available
> 1000 mm²/s

Americal Viscosity > 1000 mm/5

Dynamic viscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%)
Softening Point
Molecular weight
No information available
No information available

VOC Content (%) <= 70 g/L

Density
No information available
Bulk density
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020 Revision Number 2.01

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep from freezing.

10.5. Incompatible materials

Incompatible materials Oxidising agent.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C16-C20,	LD50 >4150 mg/kg bw (Rattus)	LD50 > 2000 mg/kg Read	
n-alkanes, isoalkanes, cyclics,	(OECD 423 Guideline)Read	Across)	
aromatics (2-30 %)	across		

Revision date 30-Jan-2020

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020 Revision Number 2.01

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Quaternary ammonium compounds, dicoco alkyldimethyl, chlorides 61789-77-3	= 960 mg/kg(Rat)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
	pianto		Iviicio organismis			(long term)
Hydrocarbons,	-	LL50 (96hr)	-	ECo (48hr)		
C16-C20, n-alkanes,		>1000 mg/kg		>1000mg/L		
isoalkanes, cyclics,		(Oncorhynchus		Daphnia magna		
aromatics (2-30 %)		mykiss) Semi		(OECD 202		
		static (Read		guideline) Read		
		across)		across		
Hydrocarbons, C9-C12,	EL50 (72h) =	10-30 mg/l	-	10-30mg/l		
n-alkanes, isoalkanes,	4.1 mg/l ((daphnia		
cyclics, aromatics	Pseudokirchner			magna)		
(2-25%)	ella subcapitata)					
RR-91855-8	OECD 401					

12.2. Persistence and degradability

Persistence and degradability No information available.

Revision date 30-Jan-2020

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

12.3. Bioaccumulative potential

Supercedes Date: 29-Jan-2020

Bioaccumulation No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe components in this formulation do not meet the criteria for classification as PBT or

vPvB.

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of

weld containers.

European Waste Catalogue 17 03 02 bituminous mixtures other than those mentioned in 17 03 01

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number UN1133 **14.2 Proper Shipping Name** Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing Group III

Description UN1133, Adhesives, 3, III, (D/E)

14.5 Environmental hazards Not applicable

14.6 Special Provisions None
Classification Code F1
Tunnel restriction code (D/E)
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler 30

Number)

IMDG

14.1 UN number UN1133 Adhesives

14.3 Transport hazard class(es) 3 14.4 Packing group III

Description UN1133, Adhesives, 3, III, (39°C c.c.)

Revision date 30-Jan-2020

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020 Revision Number 2.01

 14.5 Marine Pollutant
 Np

 14.6 Special Provisions
 223, 955

 Limited Quantity (LQ)
 5 L

 EmS-No.
 F-E. S-D

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number UN1133 **14.2 Proper Shipping Name** Adhesives

14.3 Transport hazard class(es) 3 14.4 Packing group

Description UN1133, Adhesives, 3, III

14.5 Environmental hazards Not applicable

14.6 Special Provisions A3 Limited Quantity (LQ) 10 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Revision date 30-Jan-2020

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

BOSTIK ALL WEATHER TROWEL BITUMINOUS MASTIC

Supercedes Date: 29-Jan-2020

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H372 - Causes damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects H411 - Toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

30-Jan-2020 **Revision date**

Indication of changes

Not applicable. **Revision note**

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision date 30-Jan-2020