

# DECLARATION OF PERFORMANCE


Glennon Brothers Cork Ltd.

Reference No. 0050 – CPR – 0191



1. Identification of product type
  - *Machine graded timber product with identification marking C14 or C16*
2. Type, batch or serial number or any other element identification of the construction product as required pursuant to Article 11(4).
  - *Each individual pack is identified by a unique I.D. tag attached at final processing stage.*
3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer.
  - *Machine Graded Structural Timber with rectangular cross section, EN 14081-1:2005+ A1:2011*
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required to Article 11(5).
  - *Glennon Bros. Cork Ltd, Farran South, Fermoy, Co.Cork, Ireland.*
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex ZA.
  - *2+*
6. Certification / Notified Body
  - *NSAI – 0050 for System 2+ for initial assessment of FPC and continuous surveillance of FPC- Certificate No. 0050 – CPR – 0191.*
7. Declared Performance
  - *The performance of the Machine graded structural timber is in conformity with the harmonised European Standard EN 14081-1:2005+A1:2011 Timber structures - Strength graded structural timber with rectangular cross section - Part 1: General requirements*
  - *Battens (50x35) stamped and machine graded to C14 are in compliance with S.R. 82:2017.*
8. Essential Characteristics
  - *Species / Species group – PCST / IE*
  - *Growth area- The timber is sourced from Ireland and the British Isles*
  - *Size of width range – 50mm to 250mm*
  - *Size of Thickness range – 35mm to 75mm*
  - *Surface finish – Planed & Sawn*
  - *Dry graded - DG*
  - *Grading Standard- EN 14081-1:2005+A1:2011*
  - *Strength, stiffness and density – C14 or C16(as sold and marked on the product), in accordance with EN 338:2016*
  - *Durability- Class 4*
  - *Reaction to fire – D-s2,d0*
  - *Release of dangerous substances - NPD*
9. Authorisation
  - *This declaration of performance is issued under the sole responsibility of the manufacturer identified above.*

Signed for and on the behalf of the manufacturer by:

  
Dermot Murphy  
Technical Manager

*2/12/2020*  
Date