



Bostik Rito All Weather Emergency Repair Sealant

A VERSATILE SOLVENT BASED SEALANT

Date: 22 June 2016

Fact Sheet No.:

YOUR SMART ADVANTAGES

- Versatile solvent based sealant
- Ideal for small joints and cracks
- Adheres to most wet and oily surfaces

USES

Bostik Rito All Weather Emergency Repair Sealant is a versatile solvent based sealant for small joints and cracks. After application it forms a soft plastic elastic rubber by evaporation of solvent from the sealant.

It can be used as a sealant in buildings for sealing narrow joints between window frame and wall. It can be used as a repair mastic for sealing small joints and cracks between stone, concrete and metal, for sealing leaks in gutters. It is also suitable as a steel construction mastic for sealing joint constructions in aluminium. It can also be used as a roofing sealant to bond and seal as an emergency repair. It can be used in rain or puddles and seals leaks immediately. It can be used on many materials such as lead, glass, wood, metals and stone. The product can be over painted after 24 hours. The product remains flexible for at least 20 years. For external use only.

PRODUCT CHARACTERISTICS

Colour	Black / Brown / Clear / White
Form	Solvent based non filled S-EB-S based sealant
Specific Gravity	
Composition	Solvent based sealant
Product Code	30810534 Black 300ml x 12 30810531 Brown 300ml x 12 30810532 Clear 300ml x 12 30810533 White 300ml x 12

Storage/Shelf Life	In unopened original packaging between +5°C and +25°C, shelf life 24 months. Store in dry conditions.
--------------------	---

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +40°C
Service Temperature	-25°C to +100°C
Coverage	Approx : 10 metres of 5mm diameter bead per cartridge
Drying Times	Skin formation 15 min @ 20C/55%RH
Solvent for Cleaning Up	Mechanical cleaning.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Rito Emergency Repair Sealant refer to the relevant Health & Safety Data Sheet, available at www.bostik.ie.

PREPARATION

1. Surfaces must be sound, clean and free from contaminants such as dust, oil, grease and any loose material. If necessary use a primer. Adhesion tests prior to application are recommended.
2. Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle at a 45° angle to the required diameter and screw onto the cartridge.
3. Insert the cartridge into a cartridge gun and repeatedly squeeze the trigger until the adhesive appears.



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 www.bostik.ie

APPLICATION

4. Application temperature +5C to +40C.
5. Beads 5mm in diameter are generally sufficient.

CLEANING

7. Mechanical cleaning.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Rito Emergency Repair Sealant , available at www.bostik.ie.

BOSTIK HOTLINE

Smart help +353 1 8624998



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 01 8624999	Fax: 01 8402186	orders.bostik-irl@bostik.com
Technical Advice	Tel: 01 8624998	Fax: 01 8402186	
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01 8624900	Fax: 01 8402186	



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin. Ireland. Tel: +353 1 8624900 www.bostik.ie