
NBS Specification: ROCKWOOL Rollbatt

PRODUCT SUMMARY:

Insulation roll batts.

PRODUCT GENERAL DESCRIPTION:

ROCKWOOL® Rollbatt comes pre-cut in either 400 or 600 mm width, to suit the installation scenario. The rolls provide excellent medium density thermal, fire and acoustic insulation. The products are suitable for a wide range of applications including roof spaces in all types of building and as an overlay for ceiling tiles in suspended ceilings.

FEATURES AND BENEFITS:

- Outstanding thermal, fire and acoustic properties.
- Euroclass A1 non-combustible.
- Multi-application.
- Dense, durable and robust rolls reduce slumping and sagging.
- Lightweight and easy to cut and fit.
- CE marked.

ACOUSTICS:

The incorporation of ROCKWOOL Roll, TwinRoll and Rollbatt within suitably designed constructions provides improved levels of sound reduction.

APPLICATION:

Pre-cut roll insulation with added acoustic protection and fire resistance.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

ROCKWOOL Roll Batt

PRODUCT PROPERTIES:

Standard: [d] BS EN 13162, ISO 14001

Thickness:

- 100 mm
- 150 mm

Edges: [d] Square

Thermal conductivity (maximum): [d] 0.044 W/mK.

Fire performance: [d] Euroclass A1 non-combustible

Size:

- 400 x 4800 mm - 100 mm thick.
- 600 x 4800 mm - 100 mm thick.
- 400 x 3650 mm - 150 mm thick.
- 600 x 3650 mm - 150 mm thick.

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490

www.rockwool.com/uk/