



VELUX®

Product Catalogue

Republic of Ireland Price List (excludes VAT)

1st February 2021

velux.ie



Contents

5	When the sky is the limit
6	It's our nature
8	Why VELUX®?
10	Your guide to getting daylight right
12	Our roof window features at a glance
14	Standard glazing
15	Enhanced glazing
16	News
22	Smart home
26	Roof windows
46	Combi solutions
52	Flat roof windows
72	Other ranges
80	Installation and flashings
96	Blinds and shutters
122	Accessories and practical information
130	Size and replacement

Contact us

If you'd like more information on our range of VELUX products and services, or require technical support, we're here to help.

Telephone: 01 816 1620
E-mail: sales@velux.ie

Advice on product selection and installation instructions are also available on our website velux.ie



When the sky is the limit

We know how important it is to factor daylight into your project as early as possible. For decades we have designed innovative roof windows, blinds and shutters that help create bright and welcoming spaces for your family.

From brand-new kitchen extensions and tranquil loft bedrooms to rejuvenating existing darker areas in your home – VELUX have products that are perfect for your project.

Creating the perfect indoor environment for your family isn't easy, but our products can help make this simpler. Our VELUX INTEGRA® range can be controlled by the touch of a button, our combi roof window

solutions offer maximum daylight and VELUX ACTIVE with NETATMO – our smart-home solution – will automatically open and close your electric and solar roof windows and blinds to bring in the optimum amount of daylight and fresh air.

Explore our full product range and realise how VELUX can help transform your home into a space that your whole family can grow in.



It's our nature

With our Sustainability Strategy 2030, we have made a commitment to capturing our historical CO₂ emissions and reaching carbon neutrality by 2041 – our 100-year anniversary.

Acting sustainably has always been in our nature at VELUX. That's why we are introducing a pioneering new commitment as we enter what the UN calls the Decade of Action. Our plan is to dramatically reduce our future carbon emissions in line with science and at the same time capture our entire historical carbon footprint back to the time of our founding in 1941 by protecting and restoring forests. At our centennial anniversary in 2041, we will be Lifetime Carbon Neutral.

To capture our historical carbon footprint, we have started a 20 year-long partnership with WWF (World Wide Fund for Nature) on forest and nature projects around the world.

Going forward, we will drive down our future carbon emissions by accelerating our investments in energy efficiency, shift to 100% renewable electricity, as well as substantially change the way we specify and purchase

materials for our products. In short, if you buy a VELUX roof window in 2020 and a similar window in 2030, the 2030 window will contain 50% less CO₂. By 2030 we will be a carbon neutral company and will have halved carbon emissions across our entire value chain.

When you buy a VELUX solution, you are part of this journey. You will also automatically find yourself at the forefront of roof window technology that creates better and healthier homes. For example, by applying smart sensor-based solutions to a roof window you can benefit from a self-regulating indoor climate for sustainable living indoors.

We all need a healthy home – including Mother Nature. With our new sustainability strategy, we are doing everything we can to make that happen.

Read more on [velux.ie](https://www.velux.ie)

Why VELUX®?

All over the world, VELUX roof windows contribute to healthy indoor environments by letting in fresh air and daylight. Here are six other good reasons why you should consider a VELUX roof window.

75 years of innovation

When the first VELUX roof window transformed a dark attic into a liveable space, it was a revelation. That was 75 years ago but our passion for daylight, fresh air and better living environments continues to this day and can be seen through constant innovation and award-winning design.



Extensively tested

VELUX products are designed to meet the highest quality standards and are thoroughly tested. All our roof windows are tested to withstand a year's worth of rainfall in just 15 minutes and are opened and closed 250,000 times – ensuring the products you purchase will last for decades.


10-year guarantee

We strive to ensure the quality of all VELUX products and accessories live up to our customers' exacting standards. To ensure you have peace of mind, all VELUX roof windows come with a 10-year guarantee and our range of blinds, shutters and electrical products have a 3-year guarantee. We also offer 25 years' availability on spare parts.



Fast delivery

We understand that when you order VELUX products you want them as quickly as possible. That's why you can expect to receive all standard products in just 72 hours. Specific lead times for all products are listed in the pricing tables.



Here for you

You can always call our expert team for technical support or specification advice. They're trained to give you as much in-depth assistance on planning, installation and aftercare as you need. Call us on 01 816 1620


Focused on sustainability

Sustainability is ingrained in everything we do. Not only do VELUX roof windows save energy and last for generations, but our production facilities strive to achieve zero waste, source responsibly and continually reduce environmental impact. Find out more at velux.ie

Your guide to getting daylight right

Natural light is essential to our wellbeing. The number and size of roof windows is fundamental to how your space will look and feel.

15°-90°



0°-15°



1 Identify roof pitch

VELUX roof windows can be installed in both pitched and flat roofs. Find the product that best suits your project on **p26** for sloping roof windows or **p52** for flat roof windows. New low pitch solution from 10° coming Autumn 2021.




3 Choose glazing

Get the glazing option that's right for your space - from extra noise reduction to diminish outside street noise to triple-glazing for enhanced thermal efficiency. Find out more on **p14**.

2 Get the perfect amount of daylight

For optimal comfort, we recommend that the glazed areas represent 20% of the overall floor space in your room. Learn more about optimal daylight on velux.ie/daylightcalculator



20%

Example:
15 m² x 20% = 3 m² glazing

4 Choose interior finish

VELUX roof windows come in a variety of materials to match all interior styles. Including modern white painted, moisture-resistant white polyurethane or traditional pine, you can find the perfect finish for your space.



7 Choose daylight control and heat protection

Ensure a good night's sleep and improve your indoor climate with interior blinds and/or external anti-heat blinds and shutters. Choose from a wide range of colours and designs with either manual or remote-controlled operation. See our full range of accessories on **p96**.




5 Choose roof window operation

VELUX roof windows can either be operated manually or automatically via a remote switch. The VELUX INTEGRA® range is offered in both mains powered and solar operation, perfect for areas out-of-reach.

6 Choose installation products

VELUX provide a range of flashings to suit your roofing material. They are easy to install and are designed to provide a durable, 100% watertight and weather-proof seal between the window and the roof. Find out more on **p80**.



Our roof window features at a glance

The following features come as standard with all of our roof windows and are designed to make installation and operation easier, as well as ensuring our products look their best.



1. Roof window can be rotated 180° and secured in place with **built-in barrel bolt** for easy cleaning from the inside.



5. All **standard glazing** comes with premium features like **safety lamination**, toughened glass, UV filter and our unique rain noise reduction.



2. **Ventilation bar** lets fresh air into your home even when roof window is closed.




6. **VELUX ThermoTechnology™** transfers less energy and keeps your home warm.

ThermoTechnology™



3. High quality **pivot hinges** for smooth operation.




7. **Simple red and blue line bracket** system differentiates between standard and recessed installation.




4. Straightforward blind installation with our patented **mounting brackets**.



8. **Click-on covers** make your installation easier, faster and safer.





Standard glazing



Made for
Comfort

Glazing 70
Provides great comfort with all the standard features, including rain noise reduction, laminated safety glass, protection from UV rays, and toughened glass.

✓	✓	✓	✓		
Thermal transmittance window	Uw 1.3	●●			
Thermal transmittance glazing	Ug 1.0	●●●●			
Energy transmittance	g 0.46	●●			
Sound insulation	35 dB	●●			
Layers of glass	2				



Made for
Better comfort

Glazing 68
3-layer glazing that provides all features of Comfort Glazing 70 and better energy efficiency. Helps reduce the cold that comes from a window during winter.

✓	✓	✓	✓		
Thermal transmittance window	Uw 1.1	●●●			
Thermal transmittance glazing	Ug 0.7	●●●●●			
Energy transmittance	g 0.55	●●			
Sound insulation	35 dB	●●			
Layers of glass	3				



Made for
Heat protection

Glazing 69
This 3-layer glazing filters out the heat from the sun's rays to keep your home's temperature comfortable. High thermal efficiency prevents that feeling of cold that comes from a window during winter.

✓	✓	✓	✓		
Thermal transmittance window	Uw 1.1	●●●			
Thermal transmittance glazing	Ug 0.7	●●●●●			
Energy transmittance	g 0.27	●●●●●			
Sound insulation	35 dB	●●			
Layers of glass	3				



Made for
The best noise reduction

Glazing 62D
Our highest-performing noise reduction glazing. The 2-layer glazing offers excellent reduction of sound and reduces street-noise to just a whisper. Great for homes near busy areas.

✓	✓	✓	✓		
Thermal transmittance window	Uw 1.3	●●			
Thermal transmittance glazing	Ug 1.0	●●●●			
Energy transmittance	g 0.53	●●			
Sound insulation	44 dB	●●●●●			
Layers of glass	2				

Glazing features

Rain noise reduction
Enjoy a good night's sleep without being awoken by heavy rain noise on the window.

Safety lamination
Prevents glass from falling into the room in case of accidental breakage.

Toughened glass
Adds strength to the outer pane protecting against external environmental factors.

UV filter
Protects your interior furnishings from fading due to the sun's UV rays.

Easy-to-clean
Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view.

Anti-dew
Hydrophobic coating reduces the amount of dew that can form on the outside for a clearer view.

- Good
- Very good
- Excellent
- Best



Made for
Well-being

Glazing 66
3-layer glazing that minimises the feeling of cold and blocks outside noise so you can feel warm and relaxed. Easy-to-clean and anti-dew coatings provide clearer views.

✓	✓	✓	✓	✓	✓
Thermal transmittance window	Uw 1.0	●●●			
Thermal transmittance glazing	Ug 0.6	●●●●●			
Energy transmittance	g 0.44	●●			
Sound insulation	37 dB	●●●			
Layers of glass	3				



Made for
The best experience

Glazing 67
Our best performing 3-layer glazing provides the ultimate combination of thermal efficiency and noise reduction to deliver optimal energy-efficiency and indoor comfort.

✓	✓	✓	✓	✓	✓
Thermal transmittance window	Uw 0.83	●●●●			
Thermal transmittance glazing	Ug 0.4	●●●●●			
Energy transmittance	g 0.44	●●●●●			
Sound insulation	38 dB	●●●●●			
Layers of glass	3				



Made for
Noise reduction & comfort

Glazing 62
This noise reduction window with 3-layer glazing provides up to a full 42 dB of sound reduction together with high thermal insulation. Great for homes that need additional protection from outside noise and colder weather.

✓	✓	✓	✓		✓
Thermal transmittance window	Uw 0.92 - 1.0	●●●			
Thermal transmittance glazing	Ug 0.5	●●●●●			
Energy transmittance	g 0.52	●●			
Sound insulation	42 dB	●●●●●			
Layers of glass	3				



Made for
Extra security

Glazing 70Q
This certified security window features 2-layer glazing and offers high burglary resistance. Provides additional security features built to prevent attempts of external force and breakage.

✓	✓	✓			
Thermal transmittance window	Uw 1.3	●●			
Thermal transmittance glazing	Ug 1.0	●●●●			
Energy transmittance	g 0.45	●●			
Sound insulation	35 dB				
Layers of glass	2				

U(w) - U value for the entire window

U(g) - U value for the glazing unit only

New Generation

52% more daylight

This is the future of glass rooflights

With the new generation of VELUX glass rooflights, we are continuing to raise the bar of what is possible with a flat roof window. Built with a new and unique construction, our glass rooflight range brings in more daylight than ever before and delivers minimalist and elegant glass-to-edge design; both from outside on the roof and from inside the home – so you see nothing but glass and sky.

This isn't just a new flat roof window – this is the future of flat roof windows.

Available from Summer 2021.

Maximum daylight

New design provides up to 52% more daylight*.

State-of-the-art design

Aesthetic, minimalistic design that blends seamlessly into modern home interiors. Look up, and see nothing but glass and sky.

Superb indoor comfort

Available with double or triple glazing for excellent energy performance. Combine with blackout blind for light control or anti-heat blind for heat protection and add VELUX ACTIVE with NETATMO for a healthier indoor climate.

* Daylight area. Compared to CFP/CVP 6060



News
Available from
Summer 2021





New modern collection of VELUX blinds

News
Easily update your home interior



From traditional loft spaces to modern kitchen extensions, the new VELUX blind collection has an array of colours, designs and features that will suit any interior and room type.

Developed in partnership with leading trend experts, our new blinds collection includes an extensive variety of fabrics, colours and designs. In addition to our ready-made blinds, the Colour by You collection allows you to create bespoke coloured blinds to perfectly match your space.

The VELUX blinds range includes roller blinds with flat fabrics, pleated blinds with texturised fabric – perfect for open plan extensions – and classic easy-to-clean Venetian blinds for en-suite loft bathrooms. VELUX classic blackout and duo blinds offer the ideal solution for bedrooms that need daylight-screening during the day and darkness at night.

Find out more on **p96** or at **veluxshop.ie**

White side channels now available for the entire range

In addition to the classic brushed aluminium side channels, VELUX blinds can now be ordered with white side channels in the same high-quality as the originals. They are perfect for roof windows with a white interior finish as the blind blends seamlessly into the frame.

News

Available from
September 2021

Made for low pitches

Introducing the NEW VELUX Low Pitch roof window – ideal for extension projects.

Before now, roof windows for low pitches were unable to combine function and design, but the NEW VELUX Low Pitch roof window does just that.

This window is perfect for new or existing home extensions with a roof pitch of 10°-20° and provides the same levels of daylight and fresh air as our standard pitch VELUX roof windows.

Innovation with inspiration

Created with innovative technology and design, the VELUX Low Pitch roof window is a smarter and much more stylish solution to using a flat roof kerb.

Installed the VELUX way

As with every VELUX roof window, the new VELUX Low Pitch roof window installs simply and quickly, so you can start enjoying brighter rooms right away.

Made to last

Tried and tested in northern Europe's largest wind tunnel for wind and water* resistance, VELUX low pitch roof windows are made to last.

* Winds up to 30 m/s and 120 mm rain per hour.



10°-20°

Smart home



A smarter,
healthier home



Effortless remote control of your **VELUX INTEGRA®** electric and solar roof windows and blinds



Upgrade your VELUX INTEGRA® products with **VELUX ACTIVE** for smartphone control and a healthier indoor climate

VELUX ACTIVE
WITH Netatmo



VELUX ACTIVE with NETATMO

Starter kit

VELUX ACTIVE works through live weather data and indoor climate sensors that monitor and regulate temperature, CO₂ levels, and humidity automatically. It's the perfect solution to create a healthy indoor climate for your family. It also allows you to control your roof windows and blinds from your smartphone – either via the app or by voice-control.

- Compatible with VELUX INTEGRA® roof windows, blinds and shutters
- Sensor-based operation
- Automatic heat protection
- Personal scheduling features
- Full control from smartphone app
- Easy operation with voice control
- Data security built in

days

VELUX ACTIVE			
KIX 300	VELUX ACTIVE package	203.25	5
Additional components			
KLA 300	VELUX ACTIVE indoor climate sensor	81.30	5
KLN 300	VELUX ACTIVE departure switch	40.65	5

Visit velux.ie/active to discover more. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI). All prices in EUR (€)


Details

- Monitors temperature, humidity and CO₂ levels, and ventilates your room for a comfortable and healthier indoor climate.
- Uses live weather data to ventilate proactively and shade from the sun to maintain a comfortable temperature on hot days.
- Voice-control and smart speaker integration enables you to close the blinds or shutters or open the windows just by asking.

Includes

- 1 VELUX ACTIVE Indoor Climate Sensor
- 1 VELUX ACTIVE Departure Switch
- 1 VELUX ACTIVE Gateway

See our full range of VELUX INTEGRA® roof windows starting from p32 for sloping roof windows and p56 for flat roof windows.



VELUX ACTIVE with NETATMO app



iPhone, iPod and iPad are registered trademarks of Apple Inc. Registered in the US and other countries. HomeKit is a trademark of Apple Inc. Google and Google Play are trademarks of Google LLC.

Roof windows

Centre-pivot

Page 28 for manual operation
Page 32 for electric and solar operation



Top-hung

Page 38 for manual operation
Page 40 for electric operation




Centre-pivot 3-in-1

Page 34



Manual centre-pivot, for low-pitched roofs

Page 44




VELUX CABRIO® balcony

Page 42





Roof pitch



Interior finish options



White polyurethane
Maintenance-free and moisture resistant



White painted
Bright white finish for modern interiors

Glazing options

	Double glazing --70	Triple glazing --68	Triple glazing --66	Triple glazing --62
Rain noise reduction	✓	✓	✓	✓
Safety lamination	✓	✓	✓	✓
Toughened glass	✓	✓	✓	✓
UV filter	✓	✓	✓	✓
Easy-to-clean			✓	
Anti-dew			✓	✓
Thermal transmittance of glazing (U _g -value)	1.0	0.7	0.6	0.5

Read more about glazing specifications on p14.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Out-of-reach

- If your roof windows are going to be out-of-reach, consider our VELUX INTEGRA® electric and solar range on p32.

Energy efficiency

- For an energy efficient installation that's quick and easy, take a look at our full range of installation products on p80.

Manual centre-pivot

The original roof window GGL and GGU

The classic VELUX roof window is operated by a convenient top control bar that allows you to open and close the window even with furniture placed underneath it. It also features a ventilation bar so you can air out your room but keep the window closed.

- Convenient top opening
- Easy to rotate and clean the outer glass
- Integrated ventilation behind the control bar
- Ventilation filter protects against dust and insects



External frame sizes (w×h) cm	U _w -value W/m² K	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	⌚ days
		55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	
White polyurethane												
GGU 0070	1.3	353	374	390	406	435	459	508	585	593	609	3
GGU 0068	1.1	453	474	490	506	535	559	608	685	693	709	3
GGU 0066	1.0	536	557	573	589	618	642	691	768	776	792	3
GGU 0062	0.92	631	652	668	684	713	737	786	-	871	887	9
GGU 0070Q	1.3	511	532	-	568	566	594	625	679	687	703	9
White painted												
GGL 2070	1.3	283	299	312	325	348	367	406	468	475	488	3
GGL 2068	1.1	383	399	412	425	448	467	506	568	575	588	3
GGL 2066	1.0	466	482	495	508	531	550	589	651	658	671	3
GGL 2062	0.92	561	577	590	603	626	645	684	-	753	766	9
GGL 2070Q*	1.3	377	454	-	419	457	461	500	562	569	582	9

* Special enhanced security window fitted with toughened laminated glass combined with a reinforced construction and extra locks.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie


Expand your view

Featured products GGL MK08 2070

Price: €406



Roof pitch



Interior finish options



White polyurethane
Maintenance-free and moisture resistant



White painted
Bright white finish for modern interiors

Glazing options

	Double glazing --70	Triple glazing --68	Triple glazing --66
Rain noise reduction	✓	✓	✓
Safety lamination	✓	✓	✓
Toughened glass	✓	✓	✓
UV filter	✓	✓	✓
Easy-to-clean			✓
Anti-dew			✓
Thermal transmittance of glazing (U _g -value)	1.0	0.7	0.6

Read more about glazing specifications on p14.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Home automation

- VELUX INTEGRA® products can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

VELUX INTEGRA® centre-pivot roof windows

Electric and solar powered VELUX INTEGRA® roof window
GGL and GGU

The ideal solution for out-of-reach areas, VELUX INTEGRA® roof windows are operated remotely via a wireless wall switch allowing you to open and close them with one touch. They are available in either mains or solar powered operation.

- Fully integrated motor which runs almost without a sound
- Convenient operation through a wireless wall switch
- Automatic rain sensor that closes the window when it rains
- Provides fresh air, better indoor comfort and home security



VELUX INTEGRA® mains & solar powered centre-pivot roof windows

External frame sizes (w×h) cm	U-VALUE W/m² K	CK02 55×78	CK04 55×98	CK06 55×118	MK04 78×98	FK06 66×118	MK06 78×118	MK08 78×140	UK04 134×98	PK08 94×140	SK06 114×118	⌚ days	
													□
White polyurethane													
GGU 007021U	Mains powered	1.3	703	724	740	756	785	809	858	935	943	959	3
GGU 006821U	Mains powered	1.1	803	824	840	856	885	909	958	1,035	1,043	1,059	13
GGU 006621U	Mains powered	1.0	886	907	923	939	968	992	1,041	1,118	1,126	1,142	9
GGU 007030	Solar powered	1.3	748	769	785	801	830	854	903	980	988	1,004	3
GGU 006830	Solar powered	1.1	848	869	885	901	930	954	1,003	1,080	-	1,104	3
GGU 006630	Solar powered	1.0	931	952	968	984	1,013	1,037	1,086	1,163	1,171	1,187	9
White painted													
GGL 207021U	Mains powered	1.3	633	649	662	675	698	717	756	818	825	838	3
GGL 206821U	Mains powered	1.1	733	749	762	775	798	817	856	918	925	938	13
GGL 206621U	Mains powered	1.0	816	832	845	858	881	900	939	1,001	1,008	1,021	13
GGL 207030	Solar powered	1.3	678	694	707	720	743	762	801	863	870	883	3
GGL 206830	Solar powered	1.1	778	794	807	820	843	862	901	963	-	983	13
GGL 206630	Solar powered	1.0	861	877	890	903	926	945	984	1,046	1,053	1,066	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie




Centre-pivot 3-in-1 roof window

Three windows in one frame GGLS

You can create a stunning focal point in your room with the 3-in-1 roof window. Its extra slim profile provides enhanced views and maximum daylight in any space, plus the single frame allows for easy installation.

- Provides the feeling of more space
- One frame with multiple sashes for easy installation
- Can be upgraded to solar powered operation via VELUX INTEGRA® conversion kit (KSX). Find out more on p124
- More cost effective than purchasing three single roof windows of the same size

Roof pitch



Interior finish options



White painted
Bright white finish for modern interiors

Glazing options

	Double glazing --70	Triple glazing --66
Rain noise reduction	✓	✓
Safety lamination	✓	✓
Toughened glass	✓	✓
UV filter	✓	✓
Easy-to-clean		✓
Anti-dew		✓

Thermal transmittance of glazing (U_g -value) 1.0 0.5

Read more about glazing specifications on p14.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Home automation

- If VELUX INTEGRA® solar powered conversion kits KSX are fitted, this product can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.



VELUX 3-in-1 solution*

External frame sizes (w x h) cm	U_w -value W/m ² K	FFKF06 188x118	FFKF08 188x140	days

White painted

GGLS 2066	3 roof window sashes in a single frame. Triple glazed.	1.2	1,543	1,610	3
GGLS 2070	3 roof window sashes in a single frame. Double glazed.	1.5	1,165	1,221	3

Flashing

EDWS 2000	3 roof window sashes in a single frame.		366	389	3
EDLS 2000	3 roof window sashes in a single frame.		366	389	3

VELUX 3-in-1 solution**

External frame sizes (w x h) cm	U_w -value W/m ² K	WK06 184x118	days

White painted

GGLS WK06 206650LE	3 roof window sashes in a single frame. Triple glazed.	1.2	1,543	3
GGLS WK06 207050LE	3 roof window sashes in a single frame. Double glazed.	1.5	1,165	3

Flashing

EDWS WK06 303150LE	Suitable for profiled roofing material up to 120 mm thick.		366	3
EDLS WK06 303150LE	Suitable for slate up to 8 mm thick.		366	3

* Available from April 2021.

** Available from February to April 2021. From April please order new version which has been redesigned to allow homeowners to fit electric and solar anti-heat blinds.

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie


Triple your daylight

Featured products GGLS FFKF06 2070

Price: €1,165



Roof pitch



Suitable for roof pitches between 15° and 55°. Also suitable for roof pitches between 55° and 75° with special springs. Please specify when ordering.

Interior finish options



White polyurethane
Maintenance-free and moisture resistant



White painted
Bright white finish for modern interiors

Glazing options

	Double glazing --70	Triple glazing --68	Triple glazing --66	Triple glazing --62
Rain noise reduction	✓	✓	✓	✓
Safety lamination	✓	✓	✓	✓
Toughened glass	✓	✓	✓	✓
UV filter	✓	✓	✓	✓
Easy-to-clean			✓	
Anti-dew			✓	✓
Thermal transmittance of glazing (U _g -value)	1.0	0.7	0.6	0.5

Read more about glazing specifications on p14.

Emergency escape

- Due to the unrestricted opening area, the majority of sizes are suitable for emergency escape purposes.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Manual top-hung roof windows

Outward-opening roof window GPL and GPU

VELUX top-hung roof windows are operated by a handle at the bottom of the window which opens out to 45°, providing panoramic views and a feeling of extra space. It also features a ventilation bar so you can air out your room but keep the window closed. Ideal for any loft conversion.

- Opens up the room with an uninterrupted view
- Ventilation filter protects against dust and insects
- Rotates 180° for easy cleaning off the outer glass



External frame sizes (w×h) cm	U _w -value	CK04	CK06▲	MK04▲	FK06▲	MK06▲	MK08▲	UK04▲	PK08▲	SK06▲	PK10▲	days
	W/m² K	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	94×160	
White polyurethane												
GPU 0070	1.3	484	505	527	563	595	658	-	769	790	811	3
GPU 0068	1.1	584	605	627	663	695	758	-	869	890	911	3
GPU 0066	1.0	667	688	710	746	778	841	-	952	973	994	9
GPU 0062	0.96	762	783	805	841	873	936	-	1,047	1,068	1,089	9
White painted												
GPL 2070	1.3	413	431	449	480	507	561	646	655	673	691	3
GPL 2068	1.1	513	531	549	580	607	661	746	755	773	791	3
GPL 2066	1.0	596	614	632	663	690	744	829	838	856	874	9

▲ Sizes suitable for emergency escape requirements.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie




VELUX INTEGRA® electric top-hung roof windows

Electric outward-opening VELUX INTEGRA® roof window GPU

The VELUX INTEGRA® electric top-hung roof window combines all the benefits of top-hung and effortless remote-controlled operation. It's available in mains powered operation allowing you to open and close it at ease with one touch of a switch. Ideal for any loft conversion.

- Full 45° opening allows for stunning views
- Automatic rain sensor that closes the roof window when it rains
- Provides fresh air, better indoor comfort and home security

Roof pitch



Interior finish options



White polyurethane
Maintenance-free and moisture resistant

Glazing options

	Double glazing --70	Triple glazing --66
Rain noise reduction	✓	✓
Safety lamination	✓	✓
Toughened glass	✓	✓
UV filter	✓	✓
Easy-to-clean		✓
Anti-dew		✓
Thermal transmittance of glazing (U _g -value)	1.0	0.6

Read more about glazing specifications on p14.

Compatibility

- VELUX INTEGRA® electric top-hung roof windows are only compatible with manual or solar powered blinds.
- Not compatible with twin flashings, sloping and vertical combinations, and insulated replacement flashings.
- ZWP Profile set available for use with EDN/EDJ recessed flashing kits.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Home automation

- This product can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.




External frame sizes (w×h) cm	U _w -value	FK06	FK08	MK06	MK08	PK06	PK08	SK06	SK08	days	
	W/m² K	66×118	66×140	78×118	78×140	94×118	94×140	114×118	114×140		
White polyurethane											
GPU 007021U	Mains powered	1.3	1,003	1,056	1,035	1,098	1,098	1,209	1,230	1,277	18
GPU 006621U	Mains powered	1.0	1,186	1,239	1,218	1,281	1,281	1,392	1,413	1,460	18
Profile set*											
ZWP WK06 0000		37		37		37		37			9
ZWP WK08 0000			37		37		37		37		9

* For installations (EDN, EDJ, flashings kits). Required for all recessed installations of VELUX INTEGRA® electric top-hung roof windows. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch



Interior finish options



White painted
Bright white finish for modern interiors

Glazing options

	Triple glazing --66
Rain noise reduction	✓
Safety lamination	✓
Toughened glass	✓
UV filter	✓
Easy-to-clean	✓
Anti-dew	✓

Read more about glazing specifications on p14.

Blinds and shutters

- Consider adding interior blinds for light-dimming or blackout and external blinds or shutters for heat protection.

Read more on p96.

Expand your view

- The single balcony can easily be combined with additional top-hung and fixed sloping roof windows for even more daylight.

Roof balcony

VELUX CABRIO® GDL

Transform your home and welcome in the outdoors by simply opening your VELUX CABRIO® balcony. The innovative balcony opens in seconds to give your home more space, daylight and fresh air. Consisting of a top-hung roof window and a bottom section that unfolds into a glazed balcony with elegant side banister railings, it's a balcony experience like no other.

- Top element opens outwards to 45° giving you extra headroom and beautiful panoramic views
- Transforms from a roof window into a balcony in seconds
- Side banister railings for extra safety
- Energy-efficient triple glazing is featured as standard




External frame sizes (w×h) cm	U _w -value W/m² K	MK19	MK19	PK19	PK19	SK19	SK19	days	
		78×252	166×252	94×252	198×252	114×252	238×252		
White painted									
GDL SD0L001	Including flashings for slate up to 8mm thick.	1.2	2,366	-	2,544	-	2,716	-	9
GDL SD0W001	Including flashings for tiles up to 120mm in profile.	1.2	2,366	-	2,544	-	2,716	-	9
GDL SK0L222	Including 1 x GPL & 1 x GIL and flashings for slate up to 8mm thick.	1.2	-	4,384	-	4,675	-	5,035	9
GDL SK0W224	Including 1 x GPL & 1 x GIL and flashings for tiles up to 120mm in profile.	1.2	-	4,384	-	4,675	-	5,035	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

News

Available from
September 2021



Roof pitch



Underfelt and underfelt collar



Always use underfelt and VELUX underfelt collar. VELUX underfelt collar is included in the flashing and part of the Low Pitch solution.

Interior finish options



White painted
Bright white finish for modern interiors

Glazing options

	Triple glazing -- 15
Rain noise reduction	✓
Safety lamination	✓
Toughened glass	✓
UV filter	✓
Easy-to-clean	
Anti-dew	
Thermal transmittance of glazing (U _g -value)	0.5

Blinds and shutters

- Consider blinds for light dimming or blackout, and roller shutters for heat protection.

Read more on p96.

Operation

- Can be upgraded to solar powered operation via VELUX INTEGRA® conversion kit (KSX).

Find out more on p124.

Manual centre-pivot, for low-pitch roofs

Low-pitch roof window GBL

Perfect for bringing daylight and fresh air into single-storey extensions, our brand new low-pitch roof window is the best solution for roofs with a pitch between 10°-20°. The product is designed to be totally watertight at a low pitch and features glass-to-edge technology which provides a seamless and aesthetic installation

- Tested in northern Europe's largest wind tunnel for wind and water resistance
- Fast and simple installation
- Compatible with VELUX interior blinds and external anti-heat shutter
- Flashing is suitable for profiled roofing materials up to 120mm which are suitable for roof pitches below 20 degrees



Roof windows

External frame sizes (w×h) cm	CK04	MK04	MK06	MK08	PK04	SK01	SK06	⌚ days
	55×98	78×98	78×118	78×140	94×98	114 x 70	114×118	
White painted GBL S10G01*	454	496	554	609	561	639	721	3

* Package includes window, flashing and underfelt collar suitable for installation into profiled tiles up to 120 mm. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

Combi solutions


Sloping and fixed

Page 49



Sloping and vertical


Page 50




Expand your view

Featured products:
GIL PK34 2070 with a GGL PK10 2070

Total price of this combination: €1,035



Roof pitch



Flashings

- Read more about sizes and prices for sloping extension flashings on p93.

Glazing options

	Double glazing --70	Triple glazing --68	Triple glazing --66
Rain noise reduction	✓	✓	✓
Safety lamination	✓	✓	✓
Toughened glass	✓	✓	✓
UV filter	✓	✓	✓
Easy-to-clean			✓
Anti-dew			✓

Thermal transmittance of glazing (U _g -value)	1.0	0.7	0.6

Read more about glazing specifications on p14.

Sloping and fixed

A sleek solution to increase your view

Combining VELUX roof windows can create stunning, light-filled rooms and panoramic views. If the pitch of your roof continues to the floor, you can extend your VELUX roof window by installing an additional window element below. These bottom elements have a fixed sash that cannot be opened.

Add the right sized opening window to create the perfect combination. See from p130 for available sizes.

External frame sizes (w×h) cm	U _w -value	MK34	PK34	⌚ days
	W/m² K	78×92	94×92	
White polyurethane				
GIU 0070	1.3	514	593	9
GIU 0066	1.0	697	776	9
White painted				
GIL 2070	1.3	463	534	3
GIL 2066	1.0	646	717	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Sloping and vertical combinations

More daylight and a better view VIU, VFE, VFA & VFB

Extend your views with a fixed or openable vertical window element. The window element fills the vertical space between the floor and the bottom of the roof

window to provide more expansive views and more natural daylight. Ideal for one-and-a-half storey homes.


External frame sizes (w×h) cm	U _w -value W/m ² K	MK31 78×60	MK35 78×95	⌚ days

White polyurethane		U _w -value	MK31	MK35	⌚
Product	Opening	W/m ² K	78×60	78×95	days
VIU 0070	Fixed	1.3	480	521	9
VIU 0068	Fixed	1.1	580	621	13
VIU 0066	Fixed	1.0	663	704	9
White painted		U _w -value	MK31	MK35	⌚
Product	Opening	W/m ² K	78×60	78×95	days
VFE 2070	Bottom-hung opening inwards	1.3	480	521	3
VFE 2068	Bottom-hung opening inwards	1.1	580	621	13
VFE 2066	Bottom-hung opening inwards	1.0	663	704	13
VFA 2070	Tilt and turn inwards to the left	1.3	-	571	3
VFA 2068	Tilt and turn inwards to the left	1.1	-	671	28
VFA 2066	Tilt and turn inwards to the left	1.0	-	754	3
VFB 2070	Tilt and turn inwards to the right	1.3	-	571	3
VFB 2068	Tilt and turn inwards to the right	1.1	-	671	28
VFB 2066	Tilt and turn inwards to the right	1.0	-	754	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

Roof pitch



Flashings

- Read more about sizes and prices for sloping extension flashings on p93.


Glazing options

	Double glazing --70	Triple glazing --68	Triple glazing --66
Rain noise reduction	✓	✓	✓
Safety lamination	✓	✓	✓
Toughened glass	✓	✓	✓
UV filter	✓	✓	✓
Easy-to-clean			✓
Anti-dew			✓
Thermal transmittance of glazing (U _g -value)	1.0	0.7	0.6


Read more about glazing specifications on p14.

Details


Fixed element VIU




Bottom-hung opening inwards VFE



Tilt and turn inwards to the left VFA



Tilt and turn inwards to the right VFB



Expand your view


Featured products:
GGL MK08 2070 and VFE MK35 2070

Total price of this combination: €927

Flat roof windows


New Generation – Curved glass

Page 56




New Generation – Flat glass

Page 58




Dome with glazing

Page 60




Dome

Page 62




Curved glass

Page 64




Flat glass

Page 65




Special function flat roof windows

Page 66-67




Vario by VELUX Bespoke Rooflights

Page 68



Modular skylights

Page 70



The full range of flat roof windows

We offer a complete range of flat roof windows that covers all needs. From innovative curved and flat glass rooflights to traditional domes, the VELUX flat roof window portfolio is broad and has something for everyone.

New Generation



Curved glass rooflight

Top performer with CurveTech

- Maximum daylight area
- Excellent energy performance
- State-of-the art design
- Excellent sound reduction
- Clear view and drainage with CurveTech

News
Available from Summer 2021*

(Price example 100 x 100 cm)
€1,226

See more p56 →

New Generation



Flat glass rooflight

Daylight, design & aesthetics

- Maximum daylight area
- Excellent energy performance
- State-of-the art design
- Excellent sound reduction

News
Available from April 2021

(Price example 100 x 100 cm)
€755

See more p60 →



Dome with glazing

Advanced dome solution

- Good daylight area
- Good energy performance
- Classic design
- Good sound reduction

(Price example 100 x 100 cm)
€533

See more p62 →



Dome

Without glazing. For uninhabited rooms and buildings

- Basic daylight area
- Basic energy performance

News
Available from April 2021

(Price example 100 x 100 cm)
€533

See more p62 →


Bespoke solution

- If you are looking for a bespoke solution, check out Vario by VELUX on p68.



Specifications for flat roof windows	New Generation	New Generation		
	Curved glass rooflight	Flat glass rooflight	Dome with glazing	Dome
Application areas	• Habitable rooms	• Habitable rooms	• Habitable rooms	• Uninhabited rooms and buildings, such as warehouses, garages, sheds, or industrial buildings.
Roof pitch	• 0-15°	• 2-15°	• 0-15°	• 0-15°
Design	<ul style="list-style-type: none"> • Curved glass top • 88% daylight area* • Glass-to-edge inside view • Glass-to-edge curved top • Integrated motor in frame • Discretely placed blinds • Better view – rain off CurveTech 	<ul style="list-style-type: none"> • Flat glass top • 88% daylight area* • Glass-to-edge inside view • Glass-to-edge flat top • Integrated motor in frame • Discretely placed blinds 	<ul style="list-style-type: none"> • Polycarbonate dome in clear or opaque • 70% daylight area • Integrated motor in frame 	<ul style="list-style-type: none"> • 2- or 3-layer opaque dome skins • 64% daylight area
Performance	<ul style="list-style-type: none"> • Glass top and base unit with double- or triple glazing • Insulating glass unit with inner laminated glass (P4A) • Urc,ref300: 0,65 W/(m²K)** • Arc,ref300: 4,4 m²** • Sound insulation 39 db • Burglary proof as standard*** 	<ul style="list-style-type: none"> • Glass top and base unit with double- or triple glazing • Insulating glass unit with inner laminated glass (P4A) • Urc,ref300: 0,75 W/(m²K)** • Arc,ref300: 4,1 m²** • Sound insulation 39 db • Burglary proof as standard*** 	<ul style="list-style-type: none"> • Dome skin and base unit with double glazing • Insulating glass unit with inner laminated glass (P4A) • U-value: 0,80 W/(m²K)** • Area: 3,4 m²** • Sound insulation 36 db • Burglary proof as standard*** 	<ul style="list-style-type: none"> • 2- or 3-layer opaque dome skins (no glazing) • U-value: 2,2W/(m²K)** • Area: 2,6 m²** • Sound insulation 20 db
Operation	<ul style="list-style-type: none"> • Fixed variant • Electric vented variant 	<ul style="list-style-type: none"> • Fixed variant • Electric vented variant 	<ul style="list-style-type: none"> • Fixed variant • Electric vented variant 	<ul style="list-style-type: none"> • Fixed variant • Electric vented variant
Smart home and sensors	<ul style="list-style-type: none"> • VELUX ACTIVE compatible • Pre-installed rain sensor as standard • Pre-paired wall switch • Integrated motor 	<ul style="list-style-type: none"> • VELUX ACTIVE compatible • Pre-installed rain sensor as standard • Pre-paired wall switch • Integrated motor 	<ul style="list-style-type: none"> • VELUX ACTIVE compatible • Pre-installed rain sensor as standard • Pre-paired wall switch • Integrated motor 	
Heat protection and daylight adjustment	<ul style="list-style-type: none"> • Anti-heat blind (solar) – Optimised and discrete placement • Blackout blind (solar) – Optimised and discrete placement • Insect screen (manual, cleanable, removable) 	<ul style="list-style-type: none"> • Anti-heat blind (solar) – Optimised and discrete placement • Blackout blind (solar) – Optimised and discrete placement • Insect screen (manual, cleanable, removable) 	<ul style="list-style-type: none"> • Anti-heat blind (solar) • Translucent and blackout blinds (electrical/solar) 	

* Daylight area stated as per method in EAD 220062-00-0401 (CE marking). Numbers mentioned are for a size 100100.
 ** U-value and area is stated for fixed variants with either 2-layer dome (dome), Q variant 2-layer glazing unit (dome with glazing) and 2-layer glazing unit (flat glass and curved glass). U-values and areas are calculated for window size 1.2x1.2m, with a curb height of 300 mm, in accordance with method in EN 1873:2014+A1:2016.
 *** Complies with EU legislative requirements for burglary resistance, class 2.



Roof pitch




Details

- The premium choice for home owners with 0-15° roof pitches.
- Glass-to-edge curved glass top unit.
- Unique window construction with a slim frame and invisible sash.
- Available with double or triple glazing for excellent energy performance and sound reduction.
- Laminated insulated glass unit for safety.
- Burglary resistant*.
- Comes in a fixed or electrically-vented variant.
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor.

* Complies with EU legislative requirements for burglary resistance, class 2.

Blind options

The blinds are discreetly placed in the base-unit construction, between the lower pane and outer glass, and do not compromise daylight, design or your views to the sky. See more about blinds options on p118.



Mounting of blinds is done most conveniently during the rooflight installation process.

Home automation

- The electrically-vented variant can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

Availability

- For glass rooflights available until Summer 2021, please see p64.



Flat roof windows

New Generation

Curved glass rooflight

Fixed or vented option available

Part of our new generation of rooflights, the VELUX glass rooflight with curved glass is a revolution in window design. The unique design with a slim frame and invisible sash provides maximum daylight and a beautiful design from inside the home – even with a blind installed. In addition, the curved-shaped glass top allows rainwater to easily drain off the surface – even on 0° roof pitches.

- Maximum daylight area
- Excellent energy performance
- State-of-the art design
- Excellent sound reduction
- Clear view and drainage

Available sizes (w×h) cm	U-VALUE**		060060 090060 080080 090090 100100 120090 120120								days	
	Urc.ref300 W/(m²K)	Arc.ref300 Area m²	60×60	90×60	80×80	90×90	100×100	120×90	120×120			
Top cover												
ISU 1093 Curved glass top unit			493	544	588	653	726	755	943	3		
Base												
CFU 0020Q Fixed base unit 2 layer glazing	0.65	4.4	340	375	405	450	500	520	610	3		
CFU 0025Q Fixed base unit 3 layer glazing	0.55	4.4	442	488	527	585	650	676	793	9		
CVU 0220Q Electrically-vented base unit 2 layer glazing	0.65	4.4	939	974	1,004	1,049	1,099	1,119	1,209	3		
CVU 0225Q Electrically-vented base unit 3 layer glazing	0.55	4.4	1,041	1,087	1,126	1,184	1,249	1,275	1,392	9		
Installation accessories												
ZCU 0015 Extension kerb 150mm			200	212	214	215	235	245	280	3		
ZZZ 210U Frame fixing kit			46	49	49	51	53	53	59	3		
LSF 2000 NEW Lining*			272	292	298	311	324	330	350	9		

* Lining for flat roof. This all-in-one solution includes PVC panels, vapour barrier and facings.
** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch




Details

- The elegant choice for roof pitches from 2-15°.
- Glass-to-edge flat glass top unit.
- Unique window construction with a slim frame and invisible sash.
- Available with double or triple glazing for excellent energy performance and sound reduction.
- Laminated insulated glass unit for safety.
- Burglary resistant*.
- Comes in a fixed or electrically-vented variant.
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor.

* Complies with EU legislative requirements for burglary resistance, class 2.

Blind options

The blinds are discreetly placed in the base-unit construction, between the lower pane and outer glass, and do not compromise daylight, design or your views to the sky. See more about blinds options on p118.



Mounting of blinds is done most conveniently during the rooflight installation process.

Home automation

- The electrically-vented variant can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

Availability

- For glass rooflights available until Summer 2021, please see p65.



Flat roof windows

New Generation

Flat glass rooflight

Fixed or vented option available



Part of our new generation of rooflights, the VELUX flat glass rooflight will bring the magic of daylight into your home. The unique design with a slim frame and invisible sash provides maximum daylight and a beautiful design from inside the home – even with a blind installed.

- Maximum daylight area
- Excellent energy performance
- State-of-the art design
- Excellent sound reduction

Available sizes (w×h) cm	U-VALUE**		060060	090060	080080	090090	100100	120090	120120	days
	Urc.ref300 W/(m²K)	Arc.ref300 Area m²	60×60	90×60	80×80	90×90	100×100	120×90	120×120	
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Top cover										
ISU 2093 Flat glass top unit			355	392	423	470	522	543	679	3
Base										
CFU 0020Q Fixed base unit 2 layer glazing	0.75	4.1	340	375	405	450	500	520	610	3
CFU 0025Q Fixed base unit 3 layer glazing	0.60	4.1	442	488	527	585	650	676	793	9
CVU 0220Q Electrically-vented base unit 2 layer glazing	0.75	4.1	939	974	1,004	1,049	1,099	1,119	1,209	3
CVU 0225Q Electrically-vented base unit 3 layer glazing	0.60	4.1	1,041	1,087	1,126	1,184	1,249	1,275	1,392	9
Installation accessories										
ZCU 0015 Extension kerb 150mm			200	212	214	215	235	245	280	3
ZZZ 210U Frame fixing kit			46	49	49	51	53	53	59	3
LSF 2000 NEW Lining*			272	292	298	311	324	330	350	9

* Lining for flat roof. This all-in-one solution includes PVC panels, vapour barrier and facings.
** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch




Details

- Opaque dome for optimal privacy or clear dome for daylight and view to the sky.
- PVC base unit construction provides good thermal insulation.
- Comes with double glazing.
- Laminated insulated glass unit for safety
- Burglary resistant*
- Comes in a fixed or electrically-vented variant.
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor.

* Complies with EU legislative requirements for burglary resistance, class 2.

Blind options

Considering blinds at the same time as the window is recommended. There are different blind options to choose from, both for heat protection and blackout purposes. See more about blinds options on p120.



Home automation

- The electrically-vented variant can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

Dome with glazing

Fixed or vented option available

The VELUX dome with glazing is an advanced dome solution for installation in 0-15° roof pitches. It is an effective product for letting in daylight and fresh air, without compromising on energy efficiency and comfort with sun and heat protection products. The insulated base unit has an integrated 2-layer insulating glass unit and the polycarbonate top unit is available in a clear or opaque version.

- Good daylight area
- Good energy performance
- Classic design
- Good sound reduction





Flat roof windows

Available sizes (w×h) cm	U-VALUE**		060060	060090	080080	090090	100100	090120	120120	100150	150150	days	
	W/m² K	Area	60×60	60×90	80×80	90×90	100×100	90×120	120×120	100×150	150×150		
			☐	☐	☐	☐	☐	☐	☐	☐	☐		
Top unit													
ISD 0010	Clear polycarbonate dome		214	229	241	277	301	319	391	397	542	3	
ISD 0110	Opaque polycarbonate dome		214	229	241	277	301	319	391	397	542	3	
Base unit													
CFP 0073QV	Fixed base unit	0.80	3.4	322	345	363	418	454	481	554	581	731	3
CVP 0673QV	Electrically-vented base	0.80	3.4	844	867	885	940	976	1,003	1,076	1,103	1,253	3
Installation accessories													
ZCE 0015	Extension kerb 150mm			200	212	214	223	230	232	264	276	315	3
ZZZ 210	Frame fixing kit for roof felt			46	49	49	51	53	53	59	61	72	3

** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch



Details

- Available with 2- and 3-layer opaque dome skins in polycarbonate.
- Opaque surface provides diffused daylight, improving the light needed for working.
- Choose between 15 and 30 cm up-stand.
- Comes in a fixed or electrically-vented variant.

Replacement frame

- Replace your existing, third-party dome solution with the help of a replacement frame.
- A quick and easy solution for replacement purposes.
- No need to install a new base unit.
- Fits all VELUX dome tops.


ZCJ 0000



Replacement kit for ventilation

- Turn your fixed dome solution into ventilated with this replacement kit.
- Combine with Replacement Frame to upgrade third-party domes to ventilated.

ZCJ 1210



Flat roof windows



Dome

Fixed or vented options for uninhabited rooms or buildings

The VELUX dome is a simple dome solution for uninhabited rooms or buildings, such as warehouses, garages, sheds, or smaller industrial buildings. It is available in a fixed or vented version, and with 2- or 3-layer dome skins. A motor and vented frame can be added to the fixed variant to add ventilation – even after installation. Available with fall through grid for added safety. No blinds are available for this product.

- Basic daylight area
- Basic energy performance

Available sizes (w×h) cm	U-VALUE*		060060	060090	080080	090090	100100	090120	120120	100150	150150	⌚ days			
	W/m² K	Area m²	60×60	60×90	80×80	90×90	100×100	90×120	120×120	100×150	150×150				
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
Top cover															
ISJ 0112	2 layer polycarbonate dome skin		137	174	182	260	268	297	375	471	608	3			
ISJ 0113	3 layer polycarbonate dome skin		192	245	256	365	376	418	527	662	854	3			
Base															
			2-layer		3-layer										
CFJ 0010	Fixed base unit 15 cm		2.2	1.7	2.6	164	191	209	254	265	276	326	360	456	3
CFJ 1010	Fixed base unit 30 cm		2.2	1.7	2.6	266	304	326	364	379	401	454	498	593	3
CVJ 0210	Vented base unit 15 cm		2.0	1.6	3.1	638	750	715	799	811	843	845	878	978	3
CVJ 1210	Vented base unit 30 cm		2.0	1.6	3.1	766	895	860	939	957	1,021	1,122	1,203	1,382	3
Installation accessories															
ZZZ 210J	Securing kit for roofing material		50	57	58	61	66	71	79	81	98	3			
ZCJ 0000	Replacement Frame		129	-	141	155	162	-	192	-	-	3			
ZCJ 1210	Replacement kit for ventilation		433	-	462	500	501	-	475	-	-	3			

* Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).


All prices in EUR (€)
Find all sizes and prices on velux.ie

Available until Summer 2021




CurveTech

Roof pitch



Blind options

Considering blinds at the same time as the window is recommended. There are different blind options to choose from, both for heat protection and light regulation. See more about blinds options on p18.



Home automation

- The electrically-vented variant can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

Curved glass

Fixed or vented option available

- Curved glass design ensures optimal drainage for installation in 0-15° roof pitches
- PVC base unit construction provides good thermal insulation
- Supplied with double glazing as standard
- Laminated insulated glass unit for safety
- Burglary resistance*
- Comes in a fixed or electrically-vented variant
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor

* Complies with EU legislative requirements for burglary resistance, class 2.

Available sizes (w×h) cm	U-VALUE**		060060	060090	080080	090090	100100	090120	120120	100150	days		
	Urc,ref300 W/(m²K)	Arc,ref300 Area m²	60×60	60×90	80×80	90×90	100×100	90×120	120×120	100×150			
Top cover													
ISD 1093	Curved glass top cover		449	480	506	582	632	670	822	834	3		
Base													
CFP 0073QV	Fixed flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.		0.72	3.8	322	345	363	418	454	481	554	581	3
CVP 0673QV	Electrically operated flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.		0.72	3.8	844	867	885	940	976	1,003	1,076	1,103	3
Installation accessories													
ZCE 0015	Extension kerb 150 mm		200	212	214	223	230	232	264	276	3		
ZZZ 210	Frame fixing kit for roof material		46	49	49	51	53	53	59	61	3		

** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on velux.ie

Available until Summer 2021




Roof pitch



Blind options

Considering blinds at the same time as the window is recommended. There are different blind options to choose from, both for heat protection and light regulation. See more about blinds options on p18.



Home automation

- The electrically-vented variant can be upgraded with our smart-home, sensor based system – VELUX ACTIVE with NETATMO – to create a healthier indoor climate.

Read more on p24.

Flat glass

Fixed or vented option available


- Flat glass top for installation in 2-15° roof pitch
- PVC base unit construction provides good thermal insulation
- Supplied with double glazing as standard
- Laminated insulated glass unit for safety
- Burglary resistance*
- Comes in a fixed or electrically-vented variant
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor

* Complies with EU legislative requirements for burglary resistance, class 2.


Available sizes (w×h) cm	U-VALUE**		060060	060090	080080	090090	100100	090120	120120	100150	days		
	Urc,ref300 W/(m²K)	Arc,ref300 Area m²	60×60	60×90	80×80	90×90	100×100	90×120	120×120	100×150			
Top cover													
ISD 2093	Flat glass top cover		350	375	395	454	494	523	642	652	3		
Base													
CFP 0073QV	Fixed flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.		0.79	3.4	322	345	363	418	454	481	554	581	3
CVP 0673QV	Electrically operated flat roof window base with double glazed insulating glass unit featuring laminated inner pane for safety.		0.79	3.4	844	867	885	940	976	1,003	1,076	1,103	3
Installation accessories													
ZCE 0015	Extension kerb 150 mm		200	212	214	223	230	232	264	276	3		
ZZZ 210	Frame fixing kit for roof material		46	49	49	51	53	53	59	61	3		

** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on velux.ie



Roof pitch



Details

- Note: this product is not compatible with VELUX flat roof blinds FMG, FMK and MSG.



Roof exit


The manually-operated flat roof exit window opens extra wide to provide easy access to the roof. Fully compliant with all relevant EU legislative requirements, the VELUX flat roof exit is a double-glazed roof window with a laminated inner pane that prevents glass from splintering in the event of breakage. It is available with an opaque or clear polycarbonate dome.

- Extra-large opening for easy access to the roof
- Improved comfort with low-energy double glazing
- Tilted interior frame increases daylight in the room
- Opening angle of approximately 60°
- Excellent insulating value and sound reduction


Available sizes (w×h) cm	U-VALUE**		100100	090120	120120	⌚ days	
	W/m² K	Area	100×100	90×120	120×120		
Top Cover							
ISD 0010	Clear polycarbonate dome		301	319	391	3	
ISD 0110	Opaque polycarbonate dome		301	319	391	3	
Base							
CXP 0473Q	Manually operated flat roof window base*	0.86	3.4	908	962	1,108	3
Accessories							
ZCE 0015	Extension kerb 150 mm		230	232	264	3	
ZZZ 210	Frame fixing kit for roof material		53	53	59	3	

** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie




Roof pitch



Details

- Compatible with VELUX flat roof blinds FSK and MSG. An approval by local fire authorities is needed before installation.



Smoke ventilation

The smoke ventilation flat roof window automatically opens when smoke and fire are detected to release smoke and excess heat. It can also be opened for fresh air to improve the indoor climate. Its burglar-proof construction provides additional security while a laminated inner pane prevents glass from shattering if it breaks.

- Compliant with EU legislative requirements
- Automatically opens in case of fire
- Heavy-duty reliable scissor opening mechanism
- Low-energy double glazing with two energy coatings
- Available for 0.88m² (100x100cm) or 1.30m² (120x120cm) of smoke-free ventilation area
- Tested and certified to EN ISO 12101-2
- Available for 0.88m² (100x100cm) or 1.30m² (120x120cm) of smoke-free ventilation area. Tested and certified to EN ISO 12101-2

Available sizes (w×h) cm	U-VALUE**		100100	120120	⌚ days	
	W/m² K	Area	100×100	120×120		
Smoke Ventilation System						
ISD 0010	Clear polycarbonate dome		301	391	3	
ISD 0110	Opaque polycarbonate dome		301	391	3	
Base						
CSP 1073Q	Flat roof smoke ventilation window	0.99	3.4	1,816	2,216	3
Specific smoke ventilation accessories						
KFC 210	Control unit for 1 CSP		-	678	3	
KFC 220	Control unit for 2 CSP		-	878	3	
KFA 100	Smoke detector		-	83	3	
KFK 100	Break-glass point		-	82	3	

** Calculated for a reference size of 1.2x1.2 m and 300 mm upstand, in a 0° roof pitch. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

Roof pitch



Exterior finish options



Jet Black
RAL9005

Traffic Grey
RAL7043

Rooflight options

- Fixed up to 4m²
- Opening up to 4m²
- Walk-on up to 2m²
- Round up to Ø 1350 mm
- Unlimited up to 4m² per module

Details

- The elegant choice for roof pitches from 0-15° (with a recommendation for the rooflights to be installed at a minimum pitch of 5°).
- Glass-to-edge flat glass top unit.
- Unique window construction with a slim frame and invisible sash.
- Available with double or triple glazing for excellent energy performance and sound reduction.
- Laminated insulated glass unit for safety.
- Burglary resistance*.
- Comes in a fixed or electrically-vented variant.
- Electrically-vented variant provides fresh air at the touch of a button and a pre-installed rain sensor.
- io-homecontrol compatible including VELUX remote controls and VELUX ACTIVE

* Complies with EU legislative requirements for burglary resistance, class 2.

Contact us

vario@velux.co.uk
+44 (0) 1592 778 286

Vario by VELUX

Bespoke rooflights for any project

Design and build your rooflights just the way you want them with Vario by VELUX. Use the Build Your Own configurator tool available on the Vario website to create flat roof iconic designs for your project. The tool gives you a 3D illustration of the rooflight and access to real-time prices.



- Custom-made designs for all types of project
- Huge variety of shapes, colours and features
- Sizes up to 4m² of clear internal glass

For further information visit: vario.velux.com

News

Available from
January 2021





Roof pitch



Exterior finish options



RAL7043

Details

VELUX Modular Skylights are available in a range of convenient installation packages to meet the needs of your project. For further information, please visit velux.ie/vmsdomestic.

Contact us

sales@veluxcommercial.co.uk
+44 (0)1592 778 916

Modular skylights

Open up larger roof expanses


VELUX Modular Skylights are specially designed to bring more natural light directly from above, right into the heart of your room. Modularity allows you to design with daylight over larger roof expanses for a stylish end result that blends in more with the surroundings.

- Customised for your project
- Elegant look inside and out
- Concealed electrics and motors within vented modules
- Ideal for modern flat roof homes


Other ranges

Sun tunnels

For sloped roofs
Page 74



For flat roofs
Page 76




Conservation

Top-hung or Centre-pivot
Page 77




Cold room

Side opening
Page 78




Smoke ventilation

Page 79






Roof pitch



Tunnel options

Rigid




Flexible



EdgeGlow Light Diffuser

- Our EdgeGlow light diffuser spreads natural light from the sun tunnel throughout the room.

See image on p75.



Sun tunnels for sloping roofs

Rigid and flexible tunnel options available

Add natural light to spaces where you never felt it was possible with VELUX sun tunnels. Perfect for windowless bathrooms, walk-in wardrobes and hallways.

Use rigid sun tunnels when there is direct access between the roof and the ceiling of the room. Flexible sun tunnels should be used when there is an object, such as a beam, restricting access.

Rigid sun tunnel

- Rigid sun tunnels are recommended for maximum daylight
- Recommended tunnel length 0.9-6m
- 1.7m tunnel supplied (ZTR extensions are available)
- Available in 10 and 14 inch diameters

Flexible sun tunnels for sloped roofs

- Recommended tunnel length is 1.5m
- 2m tunnel supplied
- Available in 14 inch diameter

Tunnel Diameter	10"/25 cm	14"/35 cm	
External frame size (w×h) cm	37×37	46×46	days



Rigid Sun Tunnels

TWR 0K10 2010	10" diameter rigid tunnel for tiles up to 120mm in profile.	336	-	3
TLR 0K10 2010	10" diameter rigid tunnel for slate up to 8mm thick.	336	-	3
TWR 0K14 2010	14" diameter rigid tunnel for tiles up to 120mm in profile.	-	386	3
TLR 0K14 2010	14" diameter rigid tunnel for slate up to 8mm thick.	-	386	3

Flexible Sun Tunnels

TWF 0K14 2010	14" diameter flexible tunnel for tiles up to 120mm in profile.	-	331	3
TLF 0K14 2010	14" diameter flexible tunnel for slate up to 8mm thick.	-	331	3

Accessories


ZTR 0K10 0062	600 mm extension section for 10" rigid diameter sun tunnel.	71	-	3
ZTR 0K14 0062	600 mm extension section for 14" rigid diameter sun tunnel.	-	71	3
ZTR 0K14 0124	1,200 mm extension section for 14" rigid diameter sun tunnel.	-	137	3
ZTL 014	Low-energy light kit for 10" and 14", fits inside tunnel, requires mains connection. Bulb supplied.	-	88	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie




Roof pitch



Tunnel options

Flexible



EdgeGlow light diffuser

- Our EdgeGlow light diffuser spreads natural light from the sun tunnel throughout the room.

See image on p75.

Sun tunnels for flat roofs

Flexible tunnel

Used for installation in flat roofs to bring natural light into areas of the house where a flat roof window installation is either not possible or not appropriate. The frame is made of white PVC. Supplied with polycarbonate dome.

Flexible sun tunnels

- Recommended for lengths between 0.2m and 0.9m for flat roofs
- 0.9m tunnel supplied

Tunnel Diameter (∅) cm	14"/35cm	🕒
External frame size (w×h) cm	60×60	days

Flat Roof Sun Tunnels

TCF 0K14 1010	14" diameter flat roof flexible tunnel with polycarbonate cover.	405	3
---------------	--	-----	---

Accessories

ZTL 014	Low-energy light kit for 10" and 14", fits inside tunnel, requires mains connection. Bulb supplied.	88	9
---------	---	----	---

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie




Roof pitch

Centre-pivot, top operated



Top-hung, bottom operated *



* The window is suitable for roof pitches between 15°-55°, also suitable for roof pitches between 55° and 75° with special springs.

Interior finish options



White painted
Bright white finish for modern interiors

Glazing options

	Double glazing --70
☁ Rain noise reduction	✓
🛡 Safety lamination	✓
🔨 Toughened glass	✓
☀ UV filter	✓
🧽 Easy-to-clean	
💧 Anti-dew	

Thermal transmittance of glazing (U_g-value) 1.0

Read more about glazing specifications on p14.

Conservation

Conservation roof windows with glazing bar

Conservation roof windows are the perfect choice when planning dictates that a window of traditional external appearance is required. Its black exterior profiles and glazing bar blend seamlessly into the roof and match the original look of the building. It has the same technical features as a standard VELUX roof window.

- Available in both centre-pivot and top-hung
- RAL colour 9005

External frame sizes (w×h) cm	U _w -value W/m ² K	CK04	CK06	FK06	MK06	MK08	UK04	🕒 days
		55×98	55×118	66×118	78×118	78×140	134×98	

Centre-pivot white painted

GGL SD5N2	GGL 2570 roof window + EDN recessed flashing for slate up to 8mm thick (min 20°).	1.3	554	575	636	669	721	838	3
GGL SD5P2	GGL 2570 roof window + EDP flashing for plain tiles up to 14mm thick (min 25°).	1.3	491	508	565	596	642	749	3
GGL SD5W2	GGL 2570 roof window + EDW flashing for tiles up to 120mm in profile (min 15°).	1.3	491	508	565	596	642	749	3
GGL SD5J2	GGL 2570 roof window + EDJ recessed flashing for tiles up to 90mm in profile (min 20°).	1.3	554	575	636	669	721	838	3

Top-hung white painted


GPL SD5N2	GPL 2570 roof window + EDN recessed flashing for slate up to 8mm thick (min 20°).	1.3	-	-	-	-	876	-	3
GPL SD5P2	GPL 2570 roof window + EDP flashing for plain tiles up to 14mm thick (min 25°).	1.3	-	-	-	-	797	-	3
GPL SD5W2	GPL 2570 roof window + EDW flashing for tiles up to 120mm in profile (min 15°).	1.3	-	-	-	-	797	-	3
GPL SD5J2	GPL 2570 roof window + EDJ recessed flashing for tiles up to 90mm in profile (min 20°).	1.3	-	-	-	-	876	-	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch



Glazing options

	--00	--59
Rain noise reduction		
Safety lamination		
Toughened glass		✓
UV filter		
Easy-to-clean		
Anti-dew		

Cold room

Cold room windows GVK, GVT

VELUX cold room windows are designed for use in uninhabited rooms where easy access to the roof and regular ventilation is needed. Side-hung, it opens to the left or right depending on your preference. The window is made from maintenance-free aluminium and polyurethane and comes with integrated flashing.

- Three ventilation positions for constant low-level air flow
- Patented opening restrictor securely holds the window open at 90°
- Safe roof access using the moulded tread with grooves (GVT)
- Extruded aluminium sash which can be hinged on both sides


External frame sizes (w×h) cm	U _w -value W/m² K	U _w -value		days
		46×61	54×83	
Black polyurethane				
GVT 103 0059Z	3.1	-	213	3
GVK 0000Z	5.1	157	-	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie



Roof pitch



For geometric smoke ventilation, system is certified to EN ISO12101-2 for roof pitches between 15-90. For aerodynamic smoke ventilation, system is certified to EN ISO12101-2 for roof pitches between 15-60.

Interior finish options



White polyurethane
Maintenance-free and moisture resistant

Glazing options

	Double glazing --70	Triple glazing --66
Rain noise reduction	✓	✓
Safety lamination	✓	✓
Toughened glass	✓	✓
UV filter	✓	✓
Easy-to-clean		✓
Anti-dew		✓
Thermal transmittance of glazing (U _g -value)	1.0	0.6

Read more about glazing specifications on p14.

Smoke ventilation sloping roof window

Electric smoke ventilation roof windows GGL and GGU

A VELUX smoke ventilation window is designed to automatically open when smoke is detected to quickly release smoke and excess heat. It can also be opened to let in fresh air for improved indoor comfort. The VELUX smoke ventilation window is extensively tested and compliant with all EU requirements.

- Available for 1m² (SK06 size) or 1.5m² (UK08 size) of smoke-free ventilation area
- Opens to full fire position within just 60 seconds
- Compliant with current and expected future CE standards
- System can be upgraded to comply with aerodynamic smoke ventilation requirements by the inclusion of the optional KFD external wind deflector

External frame sizes (w×h) cm	U _w -value W/m² K	SK06	UK08	days	
		114×118	134×140		
White polyurethane					
GGU SD0L140	GGU 0070 electric window + flashings for slate up to 8mm thick. Supplied with 1 smoke sensor, 1 break glass point and 1 wall control unit (KFX 210).	1.3	1,876	1,991	3
GGU SD0W140	GGU 0070 electric window + flashings for tiles up to 120mm in profile. Supplied with 1 smoke sensor, 1 break glass point and 1 wall control unit (KFX 210).	1.0	1,876	1,991	3
Accessories					
KFA 100	Smoke sensor	-	83	3	
KFK 100	Break glass unit	-	82	3	

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

Installation and flashings

Installation products

Page 83

Flashings

Standard flashings

Page 86

Recessed flashings


Page 88

Flashings for combinations and extensions

Page 90

Replacement flashings

Page 94






Underfelt collar BFX



Insulation collar BDX



Vapour barrier BBX

Installation products

Our range of installation products are made to measure, making it quick and easy for you to complete an energy efficient installation.

Underfelt collar BFX

- Ensures a watertight seal between the roof window and the roof
- Made from diffusion open material to minimise the risk of condensation
- Comes with transverse drainage gutter to lead water away from the head of the roof window if a tile or slate is broken above the window

Insulation collar BDX

- Insulates around the roof window frame, reducing heat loss and eliminating cold bridges
- Flexible insulation frame can be compressed for quick installation
- Supplied with BFX underfelt collar
- Click fittings ensure a fast and accurate assembly

Vapour barrier BBX

- Helps prevent condensation from forming in the roof structure
- A fully welded rubber gasket with a double pressure seal guarantees speedy installation and a vapour and airtight solution
- Reinforced corners for extra security against perforation

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	⌚
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	days
	□	□	□	□	□	□	□	□	□	□	

Installation Products

BBX 0000	24	25	26	27	27	28	30	31	31	31	3
BDX 2000	34	35	36	38	38	40	41	43	43	43	3
BDX 2011	68	70	73	76	76	79	83	87	86	87	3
BDX 2011E	68	70	73	76	76	79	83	87	86	87	3
BFX 1000	23	24	25	26	26	27	29	30	30	30	3


Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on velux.ie

Guide to using VELUX flashing kits

VELUX flashing kits are designed to integrate your VELUX roof window perfectly into the roofing material, ensuring that your roof window is completely weathertight, whatever the conditions.

We offer a range of flashings designed for different roofing materials and provide two options for installation height.



Standard roof window flashings


Standard installation height – install the brackets at the top and the bottom of the window frame, at the red line level.



Recessed flashings

Recessed flashings provide a sleek and streamlined finish as the roof window is installed 40 mm deeper into the roof structure, meaning that less of the roof window protrudes above the roofline. We recommend BDX insulation collar and BFX underfelt collar, included in EDN and EDJ 2000, for optimum energy efficiency.

Recessed installation height – install the brackets at the sides of the roof window frame, at the blue line level.






EDW



EDL

Roof pitch



- EDW 15°-90°
- EDL 15°-90°
- EDP 25°-90°
- EDT 20°-90°



EDP



EDT



Standard flashings

We provide a range of flashing options to suit your roofing material.

Profiled roofing material EDW

- For profile roofing material up to 120 mm
- Suitable for interlocking slate, thatch and profiled sheeting
- EDW 2000 variants come with installation products included
- Roof pitches from 15°-90°

Slate EDL

- For slate up to 8 mm thick
- Not for interlocking slate. See EDW for details
- EDL 2000 variants come with installation products included
- Roof pitches from 15°-90°

Plain tiles EDP

- For plain tiles (max length 300 mm)
- Maximum thickness of 14 mm
- Roof Pitches from 25°-90°

Flat tiles EDT

- For flat tiles 15-40 mm thick
- Designed for neater finish
- EDT 2000 variants come with installation products
- Roof pitches from 20°-90°

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	Ⓛ days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Single Window Flashings including Insulation Products (BDX 2000)

EDW 2000	92	94	98	105	105	110	116	131	126	125	3
EDL 2000	92	94	98	105	105	110	116	131	126	125	3
EDT 2000	95	97	101	108	108	113	120	136	131	130	3

Single Window Flashings

EDW 0000	63	64	67	72	72	76	81	95	90	89	3
EDP 0000	63	64	67	72	72	76	81	95	90	89	3
EDL 0000	63	64	67	72	72	76	81	95	90	89	3
EDT 0000	66	67	70	76	76	79	85	100	95	94	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all flashing types, sizes and prices on velux.ie



Roof pitch



EDN



EDJ



Recessed flashings

We provide a range of flashing options to suit your roofing material.

Slate EDN

- For slate up to 8 mm thick
- EDN 2000 includes BDX 2000F insulation package as standard
- Not for interlocking slate
- Roof pitches from 20°-90°

Flat or profiled roofing material EDJ

- For flat or profiled roofing material up to 90 mm in profile
- EDJ 2000 includes BDX 2000F insulation package as standard
- Roof pitches from 20°-90°


External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	⌚
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	days
Recessed Flashings including Installation Products											
EDN 2000	149	153	159	170	170	177	187	212	204	203	3
EDJ 2000	149	153	159	170	170	177	187	212	204	203	3
Recessed Flashings											
EDN 0000	93	95	99	107	107	112	119	141	133	132	3
EDJ 0000	93	95	99	107	107	112	119	141	133	132	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all flashing types, sizes and prices on velux.ie



Roof pitch



EDW 15°-90°
EDL 15°-90°
EDP 25°-90°

Fully customisable

- Combine the VELUX roof windows that match your needs
- Available in centre-pivot and top-hung variants
- Choose from a wide range of sizes
- Available in polyurethane, white-painted and clear lacquer finishes

Blinds and shutters

- Consider interior blinds for light dimming or blackout, and awning blinds or shutters for heat protection

[Read more on page 96](#)

Home automation

- If this combination includes VELUX INTEGRA® roof windows, it can be upgraded with a VELUX ACTIVE with NETATMO kit for full sensor-based automation

[Read more on page 24](#)

Side-by-side installation pack and flashings for combination roof windows

If you want to use multiple VELUX roof windows in your room, VELUX combination flashings give you the interconnectivity needed for easy installation. They are designed for all combinations of VELUX roof windows and give a watertight installation.

- For multiple VELUX roof windows
- High-quality watertight installation



Twin side-by-side combination

Coupled side-by-side combination

Side-by-Side Installation pack

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Flashing for 18 mm frame gap

EBW 4021B	348	357	375	400	399	415	441	503	485	482	9
EBL 4021B	348	357	375	400	399	415	441	503	485	482	9
EBP 4021B	348	357	375	400	399	415	441	503	485	482	9

Flashing for 100 mm frame gap

EKW 4021E	348	356	375	399	399	416	441	504	484	482	9
EKL 4021E	348	356	375	399	399	416	441	504	484	482	9
EKP 4021E	348	356	375	399	399	416	441	504	484	482	9

Twin & Combination Flashings

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Flashing for 18 mm frame gap

EBL 0021B Twin	141	144	151	162	162	170	181	214	203	201	9
EBW 0021B Twin	141	144	151	162	162	170	181	214	203	201	9
EBP 0021B Twin	141	144	151	162	162	170	181	214	203	201	13

Flashing for 50 mm frame gap

EBL 0021C Twin	141	144	151	-	-	-	-	-	-	201	9
EBW 0021C Twin	141	144	151	162	162	170	181	-	203	201	9

Flashing for 100 mm frame gap

EKL 0021E Coupled	144	147	154	166	166	174	185	219	207	205	3
EKW 0021E Coupled	144	147	154	166	166	174	185	219	207	205	3
EKP 0021E Coupled	144	147	154	166	166	174	185	219	207	205	3
EKN 0021E Coupled Recessed	236	255	252	273	270	284	304	358	338	336	9
EKJ 0021E Coupled Recessed	236	240	252	270	270	284	304	358	338	336	9

* Side-by-side Installation pack includes flashing, bearing beams, BDx – Insulation collar, BFX – Underfelt collar & click-on cover plate for frame gap between the roof windows.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all flashing types, sizes and prices on velux.ie



Duo combination



Triple combination



Quattro combination



Sloping and fixed



Sloping and vertical

Duo combination

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Duo flashings

	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
EKL S0122 Duo	157	160	167	180	180	189	202	237	225	222	9
EKW S0122 Duo	157	160	167	180	180	189	202	237	225	222	9

Triple combination

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Triple flashings

	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
EKL S0312 Triple	216	221	231	249	249	261	278	328	311	308	9
EKW S0312 Triple	216	221	231	249	249	261	278	328	311	308	9

Quattro combination

External frame sizes (w×h) cm	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	

Quattro flashings

	CK02	CK04	CK06	MK04	FK06	MK06	MK08	UK04	PK08	SK06	🕒 days
EKL S0222 Quattro	332	339	354	382	382	400	427	503	477	471	9
EKW S0222 Quattro	332	339	354	382	382	400	427	503	477	471	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all flashing types, sizes and prices on velux.ie

Sloping and fixed

External frame sizes (w×h) cm	MK04	MK06	MK08	UK04	PK08	SK06	🕒 days
	78×98	78×118	78×140	134×98	94×140	114×118	

Flashing for upper element

	MK04	MK06	MK08	UK04	PK08	SK06	🕒 days
EDW 0000 for profiled roofing material up to 120 mm	72	76	81	95	90	89	3
EDL 0000 for slate up to 8 mm thick	72	76	81	95	90	89	3
EDN 0000 for recessed installation into slate up to 8 mm thick	107	112	119	141	133	132	3
EDJ 0000 for recessed installation into profiled roofing material up to 120 mm	107	112	119	141	133	132	3

Flashing for extension element

	MK04	MK06	MK08	UK04	PK08	SK06	🕒 days
ETW WK34 0000 for profiled roofing material up to 120 mm	48	48	48	48	48	48	3
ETL WK34 0000 for slate up to 8 mm thick	48	48	48	48	48	48	3
ETN WK34 0000 for recessed installation into slate up to 8 mm thick	102	102	102	102	102	102	9
ETJ WK34 0000 for recessed installation into profiled roofing material up to 120 mm	110	110	110	110	110	110	9

Sloping and vertical

External frame sizes (w×h) cm	MK04	MK06	MK08	UK04	PK08	SK06	🕒 days
	78×98	78×118	78×140	134×98	94×140	114×118	

Flashing for upper element

	MK04	MK06	MK08	UK04	PK08	SK06	🕒 days
EFW 0012 for profiled roofing material up to 120 mm	126	132	141	166	158	156	9
EFL 0012 for slate up to 8 mm thick	126	132	141	166	158	156	9
EFN 0012 for recessed installation into slate up to 8 mm thick	216	227	242	285	270	268	9
EFJ 0012 for recessed installation into profiled roofing material up to 120 mm	216	227	242	285	270	268	13

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all flashing types, sizes and prices on velux.ie



EW

EL

Roof pitch



Quick and simple

- Minimal disruption as roof windows are replaced in existing aperture.
- Work can be carried out from the inside in majority of cases.
- Replacement installation usually takes under a day.
- VELUX roof window sizes are the same today as they were 30 years ago, meaning you should be able to find the right size of replacement roof window without any trouble.

For replacing single roof windows installed after April 2001 read more about standard flashing options on p86.

Type signs

- The size on this data plate will help inform you which size of replacement flashing is required as well as which size of new roof window. For roof window options, see p126-127.

Benefits of replacing your roof window

- Better energy efficiency – modern roof windows have better thermal insulation properties and are up to 115% more energy efficient.
- More light and fresh air – new VELUX roof windows have larger glazed areas and come in white finishes to match modern interiors.
- More choice, more comfort – modernise your roof windows, from improving noise reduction to controlling from your smart phone, a solution for every project.



Type signs for old roof windows manufactured before April 2001



Find a VELUX Certified Installer near you:
velux.ie/findinstaller

Replacement flashings

VELUX replacement flashings make it easy to replace VELUX roof windows without removing the existing lining. The roof windows are simply replaced in the existing aperture. This lets you enjoy a new roof window without the extra work involved in interior decoration or bathroom retiling.

Profiled roofing material EW

- For replacing a VELUX roof window manufactured before April 2001 while maintaining the original installation level of the window
- For profiled roofing material up to 120 mm

Slate EL

- For replacing a VELUX roof window manufactured before April 2001 while maintaining the original installation level of the window
- EL is a flashing for slate up to 8 mm thick

Flashing adaptor ELX

- For slate up to 8 mm thick
- The flashing adaptor kit ELX is used replacing roof window combinations and also in conjunction with standard single flashings like EDW and EDL when replacing a roof window where the internal finish is not being replaced and the roof window is placed more above the "red line" than normal.

External frame sizes (w×h) cm	CK01	CK02	CK04	MK04	FK06	MK06	MK08	UK04	PK08	SK06	PK10	UK08	days
	55×70	55×78	55×98	78×98	66×118	78×118	78×140	134×98	94×140	114×118	94×160	134×140	
For replacing single roof window installed before April 2001 window size to be replaced shown in brackets	(9)	102	(6)	304 (1)	206	306 (14)	308 (2)	804 (7)	408	606 (4)	410 (3)	808 (7)	
Replacement Window Flashings													
EL 0000	71	71	73	82	82	86	92	108	103	102	106	117	3
EW 0000	71	71	73	82	82	86	92	108	103	102	106	117	3
ELX 0000	63	63	64	72	72	76	81	95	90	89	93	102	9

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
 Find all flashing types, sizes and prices on velux.ie

Blinds and shutters

Roller blinds

Translucent and blackout
Page 98, 100, 102, 103 and 105




Duo blackout
Page 101, 103 and 105



Pleated blinds

Pleated and blackout energy
Page 106 and page 109




Venetian blind

Page 110




Insect screen

Page 111




Exterior products


Anti-heat blackout shutter
Page 115



Anti-heat blackout blind
Page 116




Anti-heat blind
Page 117





Colour options

Standard colours



Trend colours



Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Translucent roller blind

This roller blind provides basic privacy whilst still allowing in natural light. Perfect for living rooms, offices and playrooms.

- Available with white or brushed aluminium side channels
- Available in manual, mains or solar powered operation

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (wxh) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual RFL	Standard	68	70	74	78	82	84	84	86	94	114	102	110	90	108	126	7
	Trend	79	81	85	89	93	95	95	97	105	125	113	121	101	119	137	7
Mains powered RML	Standard	145	147	151	155	159	161	161	163	171	191	179	187	167	185	203	7
	Trend	156	158	162	166	170	172	172	174	182	202	190	198	178	196	214	7
Solar powered RSL	Standard	152	154	158	162	166	168	168	170	178	198	186	194	174	192	210	7
	Trend	163	165	169	173	177	179	179	181	189	209	197	205	185	203	221	7

Mains powered RML and solar powered RSL are VELUX ACTIVE compatible. Read more about VELUX ACTIVE on p24. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).


All prices in EUR (€) Find all sizes and prices on veluxshop.ie





Colour options

Standard colours



Trend colours



Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual DKL	Standard	68	70	74	78	82	84	84	86	94	114	102	110	90	108	126	7
	Trend	79	81	85	89	93	95	95	97	105	125	113	121	101	119	137	7
Mains powered DML	Standard	145	147	151	155	159	161	161	163	171	191	179	187	167	185	203	7
	Trend	156	158	162	166	170	172	172	174	182	202	190	198	178	196	214	7
Solar powered DSL	Standard	152	154	158	162	166	168	168	170	178	198	186	194	174	192	210	7
	Trend	163	165	169	173	177	179	179	181	189	209	197	205	185	203	221	7


Mains powered DML and solar powered DSL are VELUX ACTIVE Compatible. Read more about VELUX ACTIVE on p24. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on veluxshop.ie



Colour options

Standard colours



Trend colours



Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Duo blackout roller blind

A blackout roller blind and translucent pleated blind in one. It offers the best of both worlds – blackout at night and softly diffused light during the day.

- Choose any colour blackout roller blind combined with white translucent pleated blind (1016)
- Available with white or brushed aluminium side channels
- Available with manual operation

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual DFD	Standard	92	94	98	102	106	108	108	110	118	138	126	134	114	132	150	7
	Trend	103	105	109	113	117	119	119	121	129	149	137	145	125	143	161	7


Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on veluxshop.ie



Colour options

Standard colours



Installation

- Quick and easy installation with pre-fitted brackets.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.



Installation

- Quick and easy installation on VELUX roof windows.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Replacement blackout blinds

The VELUX replacement blackout blind is the perfect solution for roof windows manufactured before 2014. Ideal if you simply want to replace your old blind with a cost effective solution.

- Blackout effect
- Stepless positioning
- Only available for VELUX roof windows manufactured before 2014
- Available in 4 colours and comes with a 2 year guarantee

Most sold window sizes	CK02 C02	CK04 C04	MK04 M04	FK06 F06	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	UK08 U08	days
Sizes (w×h) cm	55×78	55×98	78×98	66×118	78×118	78×140	134×98	94×140	114×118	134×140	
DBL	48	52	58	60	60	66	80	72	76	88	3

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie

Colour by You


The Colour by You Collection lets you choose from thousands of colours to create the perfect blind to match your interior. Get inspired with our colour customisation tool at veluxshop.ie

- Available in translucent, blackout and duo blackout roller blinds
- Available in white or brushed aluminium side channels

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual operation	RFL	79	81	85	89	93	95	97	105	125	113	121	101	119	137	8
	DKL	79	81	85	89	93	95	97	105	125	113	121	101	119	137	8
	DFD	103	105	109	113	117	119	121	129	149	137	145	125	143	161	8
Mains powered	RML	156	158	162	166	170	172	174	182	202	190	198	178	196	214	8
	DML	156	158	162	166	170	172	174	182	202	190	198	178	196	214	8
Solar powered	RSL	163	165	169	173	177	179	181	189	209	197	205	185	203	221	8
	DSL	163	165	169	173	177	179	181	189	209	197	205	185	203	221	8

Mains powered DML and RML and solar powered DSL and RSL are VELUX ACTIVE compatible. Read more about VELUX ACTIVE on p24. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie



Mobile
4665



Hot air balloons
4666



Kites
4667



Universe
4653



Racing cars
4654




Roads
4655



Pink stars
4659



Blue sky
4660



Green stars
4661

Children's collection

The greatest adventures start with a good night's sleep. Blackout roller blinds and duo blackout roller blinds are available in inspirational and cheerful designs perfect for children's rooms.

Blackout roller blind

- Fabric offers complete blackout
- Available with white or brushed aluminium side channels
- Available in manual operation

Duo blackout roller blind

- Two ways to control light in one solution – blackout the room completely or soften incoming light
- Available with white or brushed aluminium side channels
- Choose any Children's Collection blackout roller blind combined with white translucent pleated blind (1016)
- Available in manual operation

Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	⌚	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140	days	
	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□		
Manual DKL or DFD	Blackout	92	94	98	102	106	108	-	110	118	138	126	134	114	132	150	8
	Duo Blackout	116	118	122	126	130	132	-	134	142	162	150	158	138	156	174	8

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie




Colour options

Standard colours




1016 1274 1259 1282


Trend colours



1276 1277 1278 1279



1280 1281 1256 1275



1283 1284 1285 1286

Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Translucent pleated blind

Decorative blinds that are an elegant way to provide privacy whilst diffusing soft natural light into your room.

- Dual control bars allow you to adjust the blind from both the top and the bottom of the roof window, letting in exactly the right amount of light (manual version only)
- Available with white or brushed aluminium side channels
- Available in manual, mains or solar powered operation

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	🕒	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140	days	
	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□		
👤 Manual FHL	Standard	68	70	74	78	82	84	84	86	94	114	102	110	90	108	126	7
	Trend	79	81	85	89	93	95	95	97	105	125	113	121	101	119	137	7
🔌 Mains powered FML	Standard	145	147	151	155	159	161	161	163	171	191	179	187	167	185	203	7
	Trend	156	158	162	166	170	172	172	174	182	202	190	198	178	196	214	7
☀️ Solar powered FSL	Standard	152	154	158	162	166	168	168	170	178	198	186	194	174	192	210	7
	Trend	163	165	169	173	177	179	179	181	189	209	197	205	185	203	221	7

Mains powered FML and solar powered FSL are VELUX ACTIVE compatible.
Read more about VELUX ACTIVE on p24.
Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).


All prices in EUR (€)
Find all sizes and prices on veluxshop.ie





Colour options

Standard colours



Trend colours



Blackout energy pleated blinds

The unique design of these blinds provides up to 25% insulation all year round. Perfect for bedrooms that need blackout at night and extra insulation.

- Free positioning in the roof window frame (manual version only)
- Available with white or brushed aluminium side channels
- Available in manual, mains or solar powered operation

Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Certifications

- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances.

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual FHC	Standard	88	90	98	102	106	110	110	112	122	148	134	142	116	140	164	7
	Trend	99	101	109	113	117	121	121	123	133	159	145	153	127	151	175	7
Mains powered FMC	Standard	165	167	175	179	183	187	187	189	199	225	211	219	193	217	241	7
	Trend	176	178	186	190	194	198	198	200	210	236	222	230	204	228	252	7
Solar powered FSC	Standard	172	174	182	186	190	194	194	196	206	232	218	226	200	224	248	7
	Trend	183	185	193	197	201	205	205	207	217	243	229	237	211	235	259	7

Mains powered FMC and solar powered FSC are VELUX ACTIVE compatible. Read more about VELUX ACTIVE on p24. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on veluxshop.ie



Colour options

Standard colour



7001

Trend colours



7057



7062



7063



7064



7065

Installation

- Quick and easy installation with pre-fitted brackets.

White line blinds

- To order the blind with white side channels, simply add WL to the end of your product code.

Details

- Unique and discreet tilt mechanism makes it very easy to tilt the slats.

Venetian blind

The classic solution for light dimming and privacy. Perfect for bathrooms.

- Moisture resistant
- Easy to clean
- Preserves your view while providing privacy
- Cordless operation
- Available with white or brushed aluminium side channels
- Available with manual operation
- Control the amount and direction of incoming light and shadows

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
Manual PAL	Standard	88	90	98	102	106	110	110	112	122	148	134	142	116	140	164	7
	Trend	99	101	109	113	117	121	121	123	133	159	145	153	127	151	175	7

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).


All prices in EUR (€)
Find all sizes and prices on veluxshop.ie



Insect screen


Enjoy fresh air without the unwanted visitors. The screen is simple to operate, and can be combined with any other VELUX interior blind. It stows neatly away in the slim aluminium top casing when not in use.

- 100% insect-proof material
- Transparent net fabric does not obstruct your view
- Durable, wind-resistant fabric for long-lasting performance



Measure

- Measure the inner wall width (A) and height (B) to find the size code and price of your insect screen
- If you have two heights (B) or heights above 2400 mm – two insect screens and one connector set ZOZ 157 SWL are needed.




Installation

- Quick and easy installation.

	A							days
	0-438 mm	439-530 mm	531-640 mm	641-760 mm	761-922 mm	923-1120 mm	1121-1285 mm	
0-1600 mm	ZIL BK04 103	ZIL CK02 102	ZIL FK08 132	ZIL MK06 120	ZIL PK25 139	ZIL SK06 156	ZIL UK04 154	5
B 1601-2000 mm	Special order	ZIL CK06 116	ZIL FK08 132	ZIL MK06 120	ZIL PK06 140	ZIL SK06 156	ZIL UK10 198	5
2001-2400 mm	Special order	Special order	ZIL FK08 132	ZIL MK10 150	ZIL PK10 155	ZIL SK10 186	ZIL UK10 198	5

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie



Discover the full range of VELUX **anti-heat blackout shutters** and **anti-heat blinds** for effective heat protection

Protection from the elements

Our wide range of VELUX exterior anti-heat solutions effectively help you to protect your home from overheating so you can enjoy a comfortable indoor climate on even the sunniest day. Discover the blind or shutter that best meets the needs for your home.



Anti-heat blackout shutter

Heat protection, blackout and insulation

See more on p115

Heat protection	● ● ● ●
Blackout	● ● ● ●
Insulation	● ●
Noise reduction	● ● ●
Prevents burglary	● ● ●




Anti-heat blackout blind

Heat protection and blackout

See more on p116

Heat protection	● ● ●
Blackout	● ● ●
Insulation	●
Noise reduction	●
Prevents burglary	●



Anti-heat blind

Heat protection and transparency

See more on p117

Heat protection	● ● ●
Blackout	●
Insulation	
Noise reduction	
Prevents burglary	



0000

Indoor climate

- Heat protection, blackout and insulation

Heat protection	● ● ● ●
Blackout	● ● ● ●
Insulation	● ●
Noise reduction	● ● ●
Prevents burglary	● ● ●

Read more about roller shutter specifications on veluxshop.ie

Anti-heat blackout shutter

From full daylight to complete blackout, these external shutters offer additional energy saving and noise reduction.

- Best heat protection and sun screening
- Total blackout
- Effective winter insulation
- Rain noise reduction
- Provides additional security and protection
- Available in mains or solar powered operation with remote control

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140	
Mains powered SML	356	356	380	392	406	410	410	426	450	490	486	494	438	510	572	7
Mains powered SMH*	-	-	-	-	-	572	-	596	630	-	680	692	-	-	-	15
Solar powered SSL	464	464	494	510	526	532	532	552	584	638	632	642	568	664	742	15

* SMH is designed for VELUX INTEGRA® top-hung roof windows. Mains powered SML and SMH and solar powered SSL are VELUX ACTIVE compatible. SSL installed on VELUX INTEGRA® solar GGL/GGU only in widths M--, P--, S-- & U--. Read more about VELUX ACTIVE on p24. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie



0000

Indoor climate

- Heat protection and blackout

	Heat protection	● ● ●
	Blackout	● ● ●
	Insulation	●
	Noise reduction	●
	Prevents burglary	●

Read more about Soft shutter specifications on veluxshop.ie

Anti-heat blackout blinds


Delivers effective heat protection by keeping your home cool on sunny days. The lightweight fabric provides blackout for a better night's sleep.

- Effective heat reduction
- Blackout effect
- Tough and durable fabric
- Available in solar powered operation with remote control

Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
	338	338	362	374	384	388	-	404	428	466	462	470	416	484	542	9	
Window size															FFKF06	FFKF08	
															188×118	188×140	
															1,167	1,212	5

Solar powered SSS is VELUX ACTIVE compatible. Read more about VELUX ACTIVE on p24. For old VELUX roof window generations (VES), a ZOZ 238 installation kit set is needed. For copper VELUX roof windows, a ZOZ 240 installation kit set is needed. For VELUX INTEGRA® GPU roof windows, a ZOZ 229S kit set is needed. SSS cannot be installed on VELUX INTEGRA® solar GGL/GGU manufactured before 2014. SSS installed on VELUX INTEGRA® solar GGL/GGU manufactured from 2014 only in widths M---, P----, S---- & U----. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on veluxshop.ie



5060

Indoor climate

- Heat protection and transparency

	Heat protection	● ● ●
	Blackout	●
	Insulation	
	Noise reduction	
	Prevents burglary	

Read more about awning blind specifications on veluxshop.ie

Anti-heat blinds

Provides heat reduction whilst ensuring you still have a view to the outside.

- Transparent fabric (14% transparency) – lets in natural light and retains the view to the outside
- Available in manual, mains or solar powered operation


Most sold window sizes	CK01 C01	CK02 C02	CK04 C04	CK06 C06	MK04 M04	FK06 F06	5	MK06 M06	MK08 M08	UK04 U04	PK08 P08	SK06 S06	PK04 P04	PK10 P10	UK08 U08	days	
Sizes (w×h) cm	55×70	55×78	55×98	55×118	78×98	66×118	70×118	78×118	78×140	134×98	94×140	114×118	94×98	94×160	134×140		
	50	50	50	50	60	60	62	60	60	82	66	78	66	66	82	7	
	232	232	248	256	264	266	266	276	292	318	316	322	284	332	372	15	
	288	288	308	318	328	332	332	344	364	396	394	400	354	414	462	15	
Window size															FFKF06	FFKF08	
															188×118	188×140	
															993	1,032	5

Installation kit required for installing MML and MSL on GPU INTEGRA® roof windows. Mains powered MML and solar powered MSL are VELUX ACTIVE compatible. Read more about VELUX ACTIVE on p24. For old VELUX roof window generations (VES), a ZOZ 238 installation kit set is needed. For copper VELUX roof windows, a ZOZ 240 installation kit set is needed. For VELUX INTEGRA® GPU roof windows, a ZOZ 229S kit set is needed. MSL cannot be installed on VELUX INTEGRA® solar GGL/GGU manufactured before 2014. MSL installed on VELUX INTEGRA® solar GGL/GGU manufactured from 2014 only in sizes M---, P----, S---- & U----. Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€) Find all sizes and prices on veluxshop.ie




Anti-heat blind
(MSU)




5070




Blackout blind
(DSU)



4550



Insect screen
(ZIU)



0000

New Generation

For curved and flat glass rooflights

Anti-heat blind

The anti-heat blind provides light dimming and heat protection to maintain a cool and comfortable room.

- Reduces overheating
- Discreetly placed inside the window
- Semi-transparent fabric for light control and sky view
- Solar powered blind with remote control
- Can be combined with an insect screen (not compatible with blackout blind)

Blackout blind

Blackout blinds block outside light for total darkness, anytime. Perfect for bedrooms and other rooms where you need complete light control.

- Perfect sleep – day or night
- Discreetly placed inside the window
- 99.9% blackout
- Great for bedrooms and media rooms
- Solar powered blind with remote control
- Can be combined with an insect screen (not compatible with anti-heat blind)

Insect screen

The insect screen lets you enjoy fresh air without any insects. It comes in a contemporary white design. It is easy to install and simple to remove for cleaning.

- Fresh air without the unwanted visitors
- 100% insect-proof
- Durable, transparent net fabric does not obstruct your view
- Can be combined with an anti-heat blind or a blackout blind



Blinds are placed inside the rooflight and mounting is therefore most convenient during the installation process.

Window size	Window size							days
	60x60	80x80	90x60	90x90	100x100	120x90	120x120	
Solar powered MSU	290	296	302	309	315	321	328	7
Solar powered DSU	290	296	302	309	315	321	328	7
Manual insect screen ZIU	66	68	69	71	72	73	75	7

Solar powered MSU is VELUX ACTIVE compatible.
Solar powered DSU is VELUX ACTIVE compatible.
Read more about VELUX ACTIVE on p24.
Blinds for flat and curved glass shown on p64-65, please see p120.

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie



Anti-heat blind

The VELUX anti-heat blind for flat roof windows provides light control and heat protection so your indoor temperature stays cool and comfortable.

6090



Translucent pleated blind




1016

1259



Blackout energy pleated blind



1045

1047



For dome with glazing*

Anti-heat blind

The VELUX anti-heat blind for flat roof windows provides light control and heat protection so your indoor temperature stays cool and comfortable.

- Reduces solar heating
- Semi-transparent fabric lets in natural light
- Slim, white-lacquered aluminium profiles
- Available in solar powered operation with remote control

Translucent pleated blind

The VELUX pleated blind for VELUX flat roof windows provides soft daylight control in a decorative folding design.

- Softly diffuses incoming natural light
- Available in mains powered operation with remote control
- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances

Blackout energy pleated blind

The VELUX blackout energy pleated blind for VELUX flat roof windows darkens the room and protects against cold.

- Light dimming and insulating effect – for greater indoor comfort
- Available in mains or solar powered operation with remote control
- OEKO-TEX® Standard 100 certified (1076-184 DTI) – contains no harmful substances

* Also compatible with Curved and Flat Glass roof windows bought before Summer 2021.

Window size	60x60	60x90	80x80	90x90	100x100	90x120	120x120	100x150	150x150	days
☀️ Solar powered MSG	□	□	□	□	□	□	□	□	□	5
🔌 Mains powered FMG										7
🔌 Mains powered FMK										7
☀️ Solar powered FSK										7

Solar powered MSG is VELUX ACTIVE compatible. Note: MSG not compatible with ISD 2093.
 Mains powered FMG is VELUX ACTIVE compatible.
 Mains powered FMK and solar powered FSK are VELUX ACTIVE compatible.
 Read more about VELUX ACTIVE on p24.
 Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
 Find all sizes and prices on veluxshop.ie

Accessories and practical information

Roof window accessories Page 124

Electric accessories
Rod controls
Locks and restrictors
Maintenance kits

Roof window replacement Page 126


How to locate your window type and size

The VELUX product code system Page 127

Practical information Page 128

VELUX installation training
Dealer information
After sales service
VELUX Rewards programme
Online professional tools
Guarantees

Size chart and replacement Page 130



Roof window accessories

Electric accessories

Power supply KUX 110

Power supply for remote operation of a VELUX INTEGRA® anti-heat shutters and blinds or interior blind on a manual roof window or fixed flat roof window [CFP].

Upgrade kit KSX 100K

Complete solar powered upgrade kit for VELUX manual centre-pivot roof window. Upgrades manual roof windows to remote operation with no wiring needed. Includes rain sensor. For windows manufactured after February 2014. Not compatible with CK01, CK02, MK27, PK25 and SK01.

Battery back up KLB 100

The battery backup ensures that if there is a power outage, VELUX INTEGRA® mains powered roof windows are closed and VELUX INTEGRA® mains powered blinds/shutters raised. It is recommended for use in regions affected by frequent power failures.

VELUX INTEGRA® wall switch – roof windows KLI 311

The wireless wall switch KLI 311 lets you conveniently open, close and stop VELUX INTEGRA® solar and mains powered roof windows, or those windows that have been upgraded for electric or solar operation. One switch can be used to operate several windows.

VELUX INTEGRA® wall switch – interior sunscreening KLI 312

The wireless wall switch KLI 312 lets you conveniently open, close and stop VELUX INTEGRA® solar and mains powered interior blinds. One switch can be used to operate several blinds.

VELUX INTEGRA® wall switch – exterior heat protection KLI 313

The wall switch KLI 313 lets you conveniently open, stop and close solar or mains powered VELUX INTEGRA® exterior anti-heat shutters and blinds. One switch can be used to operate several exterior blinds or shutters.

VELUX INTEGRA® interface KLF 200

KLF 200 is programable and can be used for operation of io-homecontrol® compatible electrical products via external control devices like switches and sensors (potential-free contacts). Can operate 5 products or 5 groups with up to 200 electrical products. Can also be used as a io-homecontrol® repeater.

Upgrade kit KSX 100

Complete solar powered upgrade kit for VELUX manual centre-pivot roof window. Upgrades manual roof windows to remote operation with no wiring needed. Includes rain sensor. For windows manufactured between April 1986 and January 2014. Not compatible with M27, P25 and 425.

Rod controls

Telescopic control rod ZCT 200K

The 100-180 cm expandable rod enables operation of VELUX manually operated centre-pivot roof windows, interior blinds and insect screens installed out-of-reach.

Control rod extension ZCT 100

Extension piece for telescopic control rod ZCT 200K, adding 100 cm to the up to 180 cm long telescopic control rod.

Interior blind adaptor ZOZ 085

Adaptor to allow remote operation of interior blind by control rod ZCT 200K.

Locks and restrictors

Security lock ZOZ 012K1

Extra security lock for VELUX centre-pivot roof windows that prevents the windows being opened from the inside without a key.

Opening restrictor with key ZOZ 010KC S011

Opening restrictor (safety latch) that prevents VELUX centre-pivot roof windows from opening more than 10 cm. Suitable for roof windows of frame height 98cm and above.

Maintenance kits

ZZZ 129KI

Professional repair kit designed to cover up marks and top finish scratches on white polyurethane roof windows.

ZZZ 130KI

Professional repair kit designed to repair marks and top finish scratches on white painted VELUX wooden roof windows.

ZZZ 131KI

Care kit for white painted VELUX roof windows. Includes special cleaner for removal of oil and grease, protector to restore the water-repellent surface and an application sponge.

ZZZ 176KI

Professional repair kit designed to repair marks and top finish scratches on clear lacquered VELUX wooden roof windows.

		days
Electric Accessories		
KUX 110	117	3
KSX 100K	278	3
KSX 100	278	5
KLB 100	167	5
KLI 311	24.39	3
KLI 312	24.39	3
KLI 313	24.39	3
KLF 200	144	5
Rod controls		
ZCT 200K	30	3
ZCT 100	18	5
ZOZ 085	7	3
Locks & Restrictors		
ZOZ 012K1	51	5
ZOZ 010KC S011	51	5
Roof window maintenance kits		
ZZZ 129KI	13	10
ZZZ 130KI	13	5
ZZZ 131KI	31	5
ZZZ 176KI	13	5

Delivery time is an approximate in working days from receipt of order placed before 11.30am (ROI).

All prices in EUR (€)
Find all sizes and prices on veluxshop.ie

Roof window replacement

Replacing a VELUX roof window is easier than you think. It can be done in as little as 4 hours, and it allows for improved energy efficiency, a better indoor climate and more daylight and fresh air.

- Same standard VELUX sizes available
- Usually fitted quickly and easily from the inside
- Minimal mess and disruption to internal finish

How to locate the roof window type and size

The same standard sizes are still available today and there are plenty of opportunities for upgrading. Flashing for replacements can be found on p94.

For advice on what type of operation and finish of roof window to select go to p12.

Find a VELUX Certified Installer near you: velux.ie/findinstaller



The VELUX product code system

All VELUX products use the following classification code system:

GGL MK06 2170 21

Window type	GGL MK06 2170 21
Window size	GGL MK06 2170 21
Interior finish	GGL MK06 2170 21
Exterior finish	GGL MK06 2170 21
Glazing	GGL MK06 2170 21
Operation	GGL MK06 2170 21



From 2014

Type Size

2001-2014

Type Size

1992-2001

Type Size

Before 1992

Type Size

Window types

GGL	Centre-pivot roof window in pine
GGLS	3-in-1 centre-pivot roof window in pine
GPU	Top-hung roof window in polyurethane, 45°
GPL	Top-hung roof window in pine, 45°
GIU	Sloping extension window element in polyurethane
GIL	Sloping extension window element in pine
VIU	Fixed vertical extension window element in polyurethane
VFE	Openable vertical window element in pine, tilt inwards
VFA	Openable vertical window element in pine, tilt and turn inwards/left-hinged
VFB	Openable vertical window element in pine, tilt and turn inwards/right-hinged
GDL	VELUX CABRIO® roof balcony
GEL	Top-hung roof terrace section in pine
VEA	Left-hinged vertical roof terrace section in pine
VEB	Right-hinged vertical roof terrace section in pine
VEC	Fixed vertical roof terrace section in pine
GVT	Side-hung craftsman's roof exit for uninhabited rooms (black polyurethane)
TWF/TLF	Flexible sun tunnel
TWR/TLR	Rigid sun tunnel
CVP	Electric flat roof window
CFP	Fixed flat roof window
CSP	Flat roof smoke ventilation window
CXP	Flat roof exit window, 60°

Window size

See all sizes on VELUX size and compatibilities chart on p130

Compatible roof windows, flashing frames, other built-in products and corresponding interior roller blinds are marked with a 'K' in the size code

Interior finish

- 0 White polyurethane
- 2 White painted wood

Exterior cover

- 0 Aluminium

Glazing

- 66 3-layer glazing for high energy efficiency with easy-to-clean and anti-dew coatings
- 67 Our best performing 3-layer glazing delivering optimal energy efficiency and indoor comfort
- 68 3-layer glazing for improved energy efficiency
- 70 2-layer glazing with rain noise reduction, laminated safety glass, UV protection and extra toughened glass

Operation

- 21U Mains powered roof window, VELUX INTEGRA®
- 30 Solar powered roof window, VELUX INTEGRA® Solar
- 40 Smoke ventilation

Practical information



VELUX installation training

We offer different kinds of training to suit your business needs. You can attend our installation and product courses online via the new VELUX Online Training Academy, at our training facilities or our mobile training unit can visit your site for tailor-made training for your team.

Find out more at velux.ie/training

Interested in becoming a VELUX Certified Installer? Go to velux.ie/certified to find out more information.



Dealer information

The easiest way to place your order is via our DealerExtranet 3.0 also known as, EDI. The DealerExtranet 3.0 offers a number of additional features, such as product and price search, quote creation, delivery track and trace and much, much more.

Sign up for DealerExtranet free of charge at velux.ie/dealernet



After sales service

Whether you want to get installation advice, ask a question about a specific product or get tips for your home improvement project, the VELUX Customer Care team is here to help:

Business customers
01 816 1620

Home owners
01 816 1620

Project support
01 816 1603



VELUX Rewards programme

You can earn rewards with a large range of VELUX products all year round! Simply sign up for a VELUX Rewards account and upload invoices for any qualifying products. Once approved, your account will be credited with points that you can spend with our large range of top-brand partners. With between €4 - €36 rewards available on most products, your points can really add up, so make sure you claim every time! Terms and conditions apply.

Register at velux.ie/rewards



Online professional tools

The VELUX website contains everything you need to know about our products and installation. The latest product information and a number of visualisation tools can be found online.

See all online tools on velux.ie/professional



Guarantees

All VELUX products and accessories are thoroughly tested to deliver the high quality you expect. In the rare event that your VELUX product doesn't meet your expectations, we offer the following guarantees:

25-year
Availability on spare parts for all products.

10-year
VELUX pitched and flat roof windows, sun tunnels and sealing products.

3-year
Electric and solar-powered external blinds and shutters.

3-year
Interior blinds and insect screens, external shutters and blinds, motors and accessories for electric and solar products.

2-year
Roof windows for uninhabited spaces.



Size and replacement

Looking to replace your existing VELUX roof window?
Use the size guide to locate your current window code
and the replacement code.

Using our size guide

VELUX current size code **MK06**

VELUX roof window type

VELUX older generation roof window size code


GGL	
GPL	14
GGU	306
GPU	M06

Cold room windows


External frame sizes (w×h) mm

	460	540
610	GVK	
830		103
		GVT


Flat-roof sun tunnel, 14", 350



Sun tunnel, 14", 350



Sun tunnel, 10", 250



FSC® certification supports good forest management where the health and safety of forest workers is secured and forest wildlife is well looked after.

Roof windows

External frame sizes (w×h) mm

	472	550	660	780	942	1140	1340
550					PK25 GGL 425 P25		
624				MK27 GGL M27			
698		CK01 9 101 GGL C01				SK01 GGL 601 S01	
778		CK02 GGL 102 GGU C02					
978	BK04 GGL 804 B04	CK04 GGL 6 GGU 104 GPU C04	FK04 GGL 204 GGU F04	MK04 GGL 1 GGU 304 GPU M04	PK04 GGL 31 GGU 404 GPU P04		UK04 GGL 7 GGU 804 GPU U04
1178		CK06 GGL 606 GGU C06	FK06 GGL 5* GGU 206 GPU F06	MK06 GGL 14 GGU 306 GPU M06	PK06 GGL 406 GGU P06	SK06 GGL 4 GGU 606 GPU S06	UK06 GGL
1398			FK08 GGL 308 GGU F08	MK08 GGL 2 GGU 308 GPU M08	PK08 GGL 408 GGU P08	SK08 GGL 10 GGU 608 GPU S08	UK08 GGL 8 GGU 808 GPU U08
1600				MK10 GGL 13 GGU 310 GPU M10	PK10 GGL 3 GGU 410 GPU P10	SK10 GGL 610 GGU S10	UK10 GGL 810 GGU U10
1800				MK12 GGL 312 GGU M12			

* GGL 5 is 700mm wide

Sloping fixed additional elements

External frame sizes (w×h) mm

	472	550	660	780	942	1140	1340
920				MK34 GIL 334 GIU M34	PK34 GIL 434 GIU P34	SK34 GIL 634 GIU S34	UK34 GIL 834 GIU U34

Centre-pivot 3-in-1

External frame sizes (w×h) mm

	1880
1178	FFKF06 GGLS
1398	FFKF08 GGLS

For 3-in-1 roof windows purchased before April 2021, please refer to p35.

Vertical elements

External frame sizes (w×h) mm

	780	942	1140	1340
600	MK31 VFE 1/2-60 VFA 331 VFB M31 VIU	PK31 VFE 431 VFB P31 VIU	SK31 VFE 631 VFB S31 VIU	UK31 VFE 831 VFB U31 VIU
954	MK35 VFE 1/2-95 VFA 334 VFB M34 VIU	PK35 VFE 434 VFB P34 VIU	SK35 VFE 634 VFB S34 VIU	UK35 VFE 834 VFB U34 VIU
1154	MK36 VFE 1/2-115 VFA 336 VFB M36 VIU	PK36 VFE 436 VFB P36 VIU	SK36 VFE 636 VFB S36 VIU	UK36 VFE 836 VFB U36 VIU
1374	MK38 VFE 338 VFA M38 VFB VIU	PK38 VFE 438 VFB P38 VIU	SK38 VFE 638 VFB S38 VIU	UK38 VFE 838 VFB U38 VIU

VELUX CABRIO® balcony

External frame sizes (w×h) mm

	780	942	1140
2520	MK19 GDL	PK19 GDL 419 P19	SK19 GDL

Flat-roof windows

External frame sizes (w×h) mm

	600	800	900	1000	1200	1500
600	060060 CFP CVU CVP CFJ CFU CVJ					
800		080080 CFP CVU CVP CFJ CFU CVJ				
900	060090 CFP CVU CVP CFJ CFU CVJ		090090 CFP CVU CVP CFJ CFU CVJ			
1000				100100 CFP CVU CVP CFJ CFU CVJ		
1200			090120 CFP CVU CVP CFJ CFU CVJ		120120 CFP CSP CFJ CVP CFU CVJ CXP CSJ	
1500				100150 CFP CVU CVP CFJ CFU CVJ CSJ		150150 CFP CFU CVP CFJ CXP CSJ

Roof terrace

External frame sizes (w×h) mm

	780
1360	M08 GEL 308
1090	M35 VEA VEB VEC 335



VELUX Company Ltd
Unit 1, Willsborough Cluster
Willsborough Industrial Estate
Clonshaugh
Dublin 17
Co Dublin

Tel: 01 816 1620

Email: sales@velux.ie
Website: velux.ie

- [facebook.com/VELUXGBI](https://www.facebook.com/VELUXGBI)
- twitter.com/VELUXGBI
- [pinterest.com/VELUXGBI](https://www.pinterest.com/VELUXGBI)
- [instagram.com/VELUX](https://www.instagram.com/VELUX)

Bringing light to life™

VELUX®

VELUX
product range